Thermaltake Toughpower GX3 SE 1000W power supply unit 24-pin ATX ATX Black

Gamintojas: **THERMALTAKE** · Modelis: **PS-TPD-1000NNSAGE-3** · EAN: **4711658549235** · Prekės kodas: **970950**



123,90 €

Kaina su PVM

Be PVM: **102,40 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt











Aprašymas

Max output current (-12V): 0.3 A | Combined power (+12V): 1000 W | Purpose: PC | Mean time between failures (MTBF): 100000 h | PCI Express power connectors (6+2 pin): 4 | Max output current (+5V): 20 A | Max output current (+5Vsb): 3 A | Motherboard power connector: 24-pin ATX | Peripheral (Molex) power cable length: 150 mm | Peripheral (Molex) power cable length: 450 | Number of SATA power connectors: 8 | Power Good signal delay range: 100 - 150 ms | Motherboard power cable length: 50 cm | SATA power cable length: 150 mm | Fan diameter: 14 cm | SATA power cable length: 450 | Combined power (+5Vsb): 15 W | PCI Express connector: Yes | Combined power (+5V): 100 W | Max output current (+3.3V): 20 A | ATX version: 3.1 | Hold time: 17 ms | Power supply unit (PSU) form factor: ATX | Max output current (+12V): 83.33 A | Combined power (-12V): 3.6 W | Combined power (+3.3V): 100 W | Power Factor Correction (PFC) type: Active | PCI Express power connectors (12+4 pin) cable length: 600 mm | Total power: 1000 W | Bearing technology: FDB | Cabling type: Non-Modular | Compliance certificates: UKCA | PCI Express power connectors (12+4 pin): 1 | Compliance certificates: CE | Efficiency: 90% | Compliance certificates: Low Voltage Directive (LVD) | Power protection features: Short circuit | Power protection features: Overheating | EPS power connector (4+4 pin): Yes | Compliance certificates: RCM | Compliance certificates: BIS | Compliance certificates: CB | Operating relative humidity (H-H): 20 - 85% | Peripheral (Molex) power connectors (4-pin): 4 | Operating temperature

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

(T-T): 5 - 40 °C | Height: 86 mm | Storage relative humidity (H-H): 10 - 95% | Width: 150 mm | AC input frequency: 50/60 Hz | Power protection features: Over voltage | Cooling type: Active | Product colour: Black | Storage temperature (T-T): -40 - 55 °C | Package type: Box | Power protection features: Under voltage | Power protection features: Over current | On/off switch: Yes | 80 PLUS certification: 80 PLUS Gold | Number of fans: 1 fan(s) | AC input voltage: 200 - 240 V | Power protection features: Over power | Input current: 10 A | Depth: 160 mm | Number of SATA power cables: 2

Techninė specifikacija

Matmenys ir svoris	
Matmenys (I × P × A)	22,00cm × 28,00cm × 13,00cm
Svoris	2,80kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.