Thermaltake Toughpower Gt power supply unit 750 W 24-pin ATX ATX Black

Gamintojas: **THERMALTAKE** · Modelis: **PS-TPT-0750FNFAGE-3** · EAN: **4711475647343** · Prekės kodas: **970951**



90,90 €

Kaina su PVM

Be PVM: **75,12 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt











Aprašymas

Certification: CE/UKCA/ICES/TUV/LVD/RCM/CB/FCC/cTUVus/BSMI/CCC/BIS/S-MARK | Number of SATA power connectors: 6 | Hold time: 17 ms | SATA power cable length: 150 mm | Max output current (-12V): 0.3 A | Max output current (+12V): 62.5 A | CPU power cable length: 70 cm | PCI Express power connectors (12+4 pin) cable length: 600 mm | Motherboard power connector: 24-pin ATX | Max output current (+5V): 20 A | Peripheral (Molex) power cable length: 400 mm | Peripheral (Molex) power cable length: 150 mm | Max output current (+5Vsb): 3 A | Power Good signal delay range: 100 - 250 ms | SATA power cable length: 450 | Motherboard power cable length: 55 cm | PCI Express power connectors (12+4 pin): 1 | Combined power (+5Vsb): 15 W | Max output current (+3.3V): 20 A | CPU power connector (4+4 pin): Yes | Input current: 10 A | Purpose: PC/Server | Bearing technology: Hydraulic | Width: 150 mm | Combined power (+5V): 100 W | AC input voltage: 100 - 240 V | Mean time between failures (MTBF): 100000 h | 80 PLUS certification: 80 PLUS Gold | AC input frequency: 50/60 Hz | Operating relative humidity (H-H): 5 - 85% | Fan diameter: 12 cm | Number of fans: 1 fan(s) | On/off switch: Yes | Combined power (-12V): 3.6 W | ATX version: 3.1 | Operating temperature (T-T): 0 - 40 °C | Depth: 140 mm | Total power: 750 W | Power supply unit (PSU) form factor: ATX | Power protection features: Short circuit | Power protection features: Over voltage | Storage temperature (T-T): -40 - 70 °C | Package type: Box | Product colour: Black | Power protection features: Under voltage

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

| Power protection features: Over current | Power protection features: Over power | Power protection features: Overheating | Cabling type: Fully-Modular | Combined power (+3.3V): 100 W | Height: 86 mm | PCI Express power connectors (6+2 pin): 4 | Cooling type: Active | Peripheral (Molex) power connectors (4-pin): 4 | Power Factor Correction (PFC) type: Active | Storage relative humidity (H-H): 5 - 95% | Combined power (+12V): 750 W

Techninė specifikacija

Matmenys ir svoris	
Matmenys (I × P × A)	29,00cm × 12,00cm × 22,00cm
Svoris	2,44kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903