Thermaltake Toughpower GT 1000W power supply unit 24-pin ATX ATX Black

Gamintojas: **THERMALTAKE** · Modelis: **PS-TPT-1000FNFAGE-3** · EAN: **4711658543981** · Prekės kodas: **970952**



137,90 €

Kaina su PVM

Be PVM: **113,97 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt











Aprašymas

Operating temperature (T-T): 0 - 40 °C | Purpose: PC | Bearing technology: Hydraulic | Operating relative humidity (H-H): 5 - 85% | AC input voltage: 100 - 240 V | Max output current (-12V): 0.3 A | Depth: 140 mm | 80 PLUS certification: 80 PLUS Gold | Product colour: Black | Combined power (+12V): 999.6 W | AC input frequency: 50/60 Hz | Storage temperature (T-T): -40 - 70 °C | Input current: 15 - 10 A | Peripheral (Molex) power connectors (4-pin): 4 | Height: 86 mm | PCI Express power connectors (6+2 pin): 5 | Number of SATA power connectors: 6 | Peripheral (Molex) power cable length: 150 mm | Width: 150 mm | Max output current (+3.3V): 20 A | Combined power (+5V): 100 W | Cooling type: Active | Combined power (+5Vsb): 15 W | On/off switch: Yes | Hold time: 17 ms | Power supply unit (PSU) form factor: ATX | Total power: 1000 W | Max output current (+12V): 83.3 A | Power Factor Correction (PFC) type: Active | Power protection features: Over power | Power protection features: Under voltage | Power protection features: Over current | Cabling type: Fully-Modular | Combined power (+3.3V): 100 W | Mean time between failures (MTBF): 100000 h | Power protection features: Short circuit | Power protection features: Over voltage | Max output current (+5Vsb): 3 A | SATA power cable length: 150 mm | Max output current (+5V): 20 A | Motherboard power cable length: 55 cm | SATA power cable length: 450 | Combined power (-12V): 3.6 W | EPS power connector (4+4 pin): Yes | Number of fans: 1 fan(s) | Peripheral (Molex) power cable length: 400 mm | Fan diameter: 12 cm | Motherboard

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

power connector: 24-pin ATX | ATX version: 3.1 | PCI Express power connectors (12+4 pin) cable length: 600 mm | Compliance certificates: Low Voltage Directive (LVD) | Compliance certificates: CCC | Compliance certificates: RCM | Compliance certificates: BIS | Compliance certificates: cTUVus | PCI Express power connectors (12+4 pin): 1 | Compliance certificates: BSMI | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: ICES | Compliance certificates: UKCA | Compliance certificates: CB | Compliance certificates: EAC

Techninė specifikacija

Matmenys ir svoris	
Matmenys (I × P × A)	13,00cm × 29,00cm × 22,00cm
Svoris	2,84kg