Thermaltake Toughpower GT 1200W power supply unit 24-pin ATX ATX Black

Gamintojas: **THERMALTAKE** · Modelis: **PS-TPT-1200FNFAGE-3** · EAN: **4711658544087** · Prekės kodas: **970953**



154,90 €

Kaina su PVM

Be PVM: **128,02 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt











Aprašymas

Compliance certificates: Federal Communications Commission (FCC) | PCI Express power connectors (12+4 pin): 2 | Compliance certificates: cTUVus | Compliance certificates: ICES | Compliance certificates: Low Voltage Directive (LVD) | Compliance certificates: UKCA | Compliance certificates: CCC | Compliance certificates: RCM | Compliance certificates: BIS | Compliance certificates: CB | Compliance certificates: EAC | Compliance certificates: CE | PCI Express power connectors (12+4 pin) cable length: 600 mm | Compliance certificates: BSMI | Power Factor Correction (PFC) type: Active | Combined power (+3.3V): 100 W | Combined power (+12V): 1200 W | AC input frequency: 50/60 Hz | On/off switch: Yes | Height: 86 mm | Bearing technology: Hydraulic | Operating relative humidity (H-H): 5 - 85% | Hold time: 17 ms | Depth: 140 mm | Max output current (+12V): 100 A | PCI Express power connectors (6+2 pin): 5 | Number of SATA power connectors: 6 | Peripheral (Molex) power connectors (4-pin): 4 | Max output current (+5Vsb): 3 A | Product colour: Black | Combined power (-12V): 3.6 W | Power supply unit (PSU) form factor: ATX | Operating temperature (T-T): 0 - 40 °C | Storage temperature (T-T): -40 - 70 °C | Cooling type: Active | Power protection features: Over power | Power protection features: Short circuit | Power protection features: Over voltage | Power protection features: Under voltage | Power protection features: Over current | Combined power (+5V): 100 W | EPS power connector (4+4 pin): Yes | Input current: 15 - 10 A | Combined power (+5Vsb): 15 W | Mean time between failures (MTBF):

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

100000 h | Max output current (+3.3V): 20 A | Cabling type: Fully-Modular | Fan diameter: 12 cm | Peripheral (Molex) power cable length: 400 mm | Motherboard power connector: 24-pin ATX | Number of fans: 1 fan(s) | ATX version: 3.1 | Total power: 1200 W | SATA power cable length: 450 | Peripheral (Molex) power cable length: 150 mm | Max output current (-12V): 0.3 A | Width: 150 mm | SATA power cable length: 150 mm | Motherboard power cable length: 55 cm | 80 PLUS certification: 80 PLUS Gold | Purpose: PC | AC input voltage: 100 - 240 V | Max output current (+5V): 20 A

Techninė specifikacija

Matmenys ir svoris	
Matmenys (I × P × A)	13,00cm × 22,00cm × 28,00cm
Svoris	3,02kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903