D-Link DPE-301GS 1 Port Gigabit 30W PoE Splitter

Gamintojas: **D-LINK** · Modelis: **DPE-301GS** · EAN: **790069416675** · Prekės kodas: **972672**



57,90 €

Kaina su PVM

Be PVM: **47,85 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Simplicity
- ✓ Plug-and-Play, so no software required
- ✓ Reduces installation and network equipment costs by removing the need for electrical wiring
- ✓ Provides power over existing network cabling when paired with a Power Source Equipment (such as the DPE-301GI) to a non-PoE device
- ✓ Flexible Power Options
- ✓ Separates a PoE Ethernet cable into DC power and a standard Ethernet cable
- ✓ Supports 5 V, 9 V, and 12 V output voltages
- ✓ Transforms incoming AC power to low-voltage DC power Gigabit Connectivity
- ✓ Receives power up to 100 metres away
- ✓ Connect your devices at Gigabit speeds









Aprašymas

The DPE-301GS PoE splitter is used with end devices such as wireless access points, IP cameras and VoIP phones that don’t natively support PoE, but rather require DC power input of 5V, 9V or 12V. It receives PoE power on a network cable from a PoE switch or midspan injector, and splits the Ethernet and DC power into two separate cables. One cable provides the DC power, and the other cable provides the Ethernet signal. Users can select from 5VDC, 9VDC and 12VDC power for their device using a selectable DIP switch on the device.

The DPE-301GS PoE splitter is typically located near the end device. It has two 10/100/1000 RJ-45 ports. One port is for PoE IN, which is the network connection and is usually connected to a remote PoE switch or injector. The other port is for LAN OUT, which is the connection that provides the

Ethernet signal to the end device. The DPE-301GS also has a 5.5mm DC OUT port. Two adapter cables are supplied; either one may be connected to this port, depending on whether 5.5mm or 3.8mm interface is required for the end device.

Techninė specifikacija

Features	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u
Power over Ethernet (PoE)	Yes
Product colour	White
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-30 - 70 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%
Certificates	
Certification	CE, FCC, VCCI, RCM
Weight & dimensions	
Weight	98 g
Packaging data	
Package width	106 mm
Package depth	156 mm
Package height	61 mm
Package weight	230 g
Power	
Output power	32.4 W
Logistics data	
Products per shipping (inner) case	40 pc(s)
Shipping (inner) case length	44.5 cm
Shipping (inner) case width	33.2 cm
Shipping (inner) case height	32.5 cm
Pallet gross length	120 cm
Pallet gross width	110 cm
Matmenys ir svoris	

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Svoris	0,25kg

Dokumentai ir vaizdo įrašai

- Greitos pradžios vadovas
- Gaminio lankstinukas
- Saugos informacija
- Atitikties deklaracija

Gamintojo ir saugos informacija

GAMINTOJAS

D-Link

ATSAKINGAS ASMUO ES

D-Link Benelux
Postbus 48, 5480 AA Schijndel, NL
dlink.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

- Atitikties deklaracija
- Saugos informacija