D-Link DGS-1210-10P Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Black

Gamintojas: **D-LINK** · Modelis: **DGS-1210-10P/E** · EAN: **790069467721** · Prekės kodas: **973500**



130.90€

Kaina su PVM

Be PVM: **108.18€**

In Stock

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Layer 2 management and security with Layer 3 capabilities
- ✓ Compact Command-Line Interface (CLI) and web-based User-Interface
- ✓ Static Routing and MSTP
- ✓ PoE options up to 370W power budget
- ✓ Dual image & config



Aprašymas

Smart Managed with a Plus

With increased PoE output, advanced Layer 2 management features, and Layer 3 static routing , D-Link’s DGS-1210 Smart+ Managed Gigabit Switches provide a cost-efficient and flexible solution for expanding any business network.

Advanced Layer 2 Management with Layer 3 Static Routing

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

The DGS-1210 Smart+ family has advanced network management options, accessible via Compact CLI or the Web-based UI, that equip your business with network capabilities such as VLANs, multiple spanning tree protocol (MSTP), link aggregation (LACP), static routing, dual software images, and dual configuration files.

With powerful security features like IGMP snooping, access control lists, port security, and the unique D-Link Safeguard Engine that protects your network against malicious denial-of-service attacks from broadcast, multicast and unicast flooding, the DGS-1210 Smart+ family is a versatile solution for access-edge network environments.

Fibre Uplinks

Use fibre uplinks to connect across longer distances, like factory lines and university campuses, using lightweight, secure, and energy-efficient fibre optic cabling that’s immune to interference and which has access to higher throughput to protect the future demands of your business network.

PoE and PoE+, with budgets up to 370W

The DGS-1210 Smart+ Series includes a range of high power budget PoE-enabled switches for business looking to power larger deployments of VoIP phones, wireless access points or network cameras.

Free Network Design and Management Software

D-Link’s free Network Assistant (DNA) displays all connected devices and speeds up the first time configuration. The free D-View 7 Network Management System comes with a license for 25 nodes and 2 probes and full access to the management tools. Optional upgrade licenses allow you to broaden your network and analysis.

Smart Energy-Saving Design

D-Link Green technology enables the DGS-1210 Smart+ series to save power without any sacrifices. The majority of the family utilises a fanless design, otherwise they feature a smart fan that powers on above a certain temperature. All come with advanced silicon technology which saves up to 73% of energy compared to a normal switch.

Surveillance Mode

Select Surveillance Mode in the Web UI to take advantage of easy-to-use surveillance features which enable you to manage your surveillance network effortlessly. It automatically detects your security devices and segments them into a dedicated Auto Surveillance VLAN to handle video surveillance traffic securely and efficiently.

Techninė specifikacija

Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0

Installed SFP+ modules quantity	0
Gigabit Ethernet (copper) ports quantity	8
SFP module slots quantity	2
Power connector	DC-in jack
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T
Cable types supported	Cat5, Cat5e
Port mirroring	Yes
Full duplex	Yes
Flow control support	Yes
Link aggregation	Yes
Auto MDI/MDI-X	Yes
Data transmission	
MAC address table	8000 entries
Switching capacity	20 Gbit/s
Forwarding rate	14.88 Mpps
Store-and-forward	Yes
Packet buffer memory	0.512 MB
Security	
Access Control List (ACL)	Yes
MAC address filtering	Yes
Multicast features	
Multicast support	Yes
Design	
Rack mounting	Yes
Stackable	Yes
Form factor	1U
Product colour	Black
LED indicators	Yes
Performance	
Noise level	0 dB
Mean time between failures (MTBF)	729258 h

Power	
Power consumption (max)	80.6 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	8
Power over Ethernet plus (PoE+) ports quantity	2
Total Power over Ethernet (PoE) budget	78 W
Operational conditions	
Operating temperature (T-T)	-5 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Heat dissipation	373.96 BTU/h
Weight & dimensions	
Width	280 mm
Depth	126 mm
Height	44 mm
Weight	950 g
Packaging data	
Package width	288 mm
Package depth	331 mm
Package height	72 mm
Package weight	2.21 kg
Certificates	
Certification	EMI: CE Class A, VCCI Class A, FCC Class A, BSMI, CCC
Matmenys ir svoris	
Matmenys (I × P × A)	33.00cm × 29.00cm × 7.00cm
Svoris	1.96kg

Dokumentai ir vaizdo įrašai

› Product leaflet

Gamintojo ir saugos informacija

MANUFACTURER

D-Link

EU RESPONSIBLE PERSON

D-Link Benelux
Postbus 48, 5480 AA Schijndel, NL
dlink.com

DISTRIBUTOR

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt