APC Smart-UPS On-Line SRT nepertraukiamo maitinimo resursai (UPS) Dviguba konversija (prisijungus) 3 kVA 2700 W

Gamintojas: **APC BY SCHNEIDER ELECTRIC** · Modelis: **SRT3000RMXLI-NC** · EAN: **731304327592** · Prekės kodas: **974097**



4 619,90 €

Kaina su PVM

Be PVM: **3 818,10 €**

Sandėlyje


Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Dviguba konversija (prisijungus)
- ✓ 3 kVA 2700 W
- ✓ Signalų forma: Sinusas
- ✓ Rūgštinis akumuliatorius (VRLA)
- ✓ Stelažas Juoda















Aprašymas

Stay always online and prevent data loss

An APC Smart-UPS On-Line always supplies perfectly clean power to all connected equipment thanks to its double conversion technology. Even power outages have no influence on this. The APC Smart-UPS On-Line then automatically supplies emergency power without having to switch. This way you prevent unwanted failure of, for example, a PC, server, storage or switch. With the APC PowerChute Network Shutdown software you can even have critical IT hardware shut down automatically and in a controlled manner when the battery of the UPS is almost empty. This way you prevent data loss, downtime and physical damage to hardware.

Extend the runtime

You can easily increase the number of minutes that the APC SRT3000RMXLI-NC can independently supply emergency power by connecting external battery packs (SRT96RMBP). A runtime of several hours is even possible.

Availability

The Smart-UPS On-Line has an internal bypass and uses double conversion, maximizing the availability and lifespan of connected hardware. It also makes the UPS compatible with an emergency power generator. The Un-
Line double conversion technology ensures clean, uninterrupted power to protected equipment even when generator power is used.

Safety

In addition, a Smart-UPS On-Line protects connected devices against peak voltage caused by lightning, among other things. This APC emergency power supply is ideally suited for business use.

Ease of use

The APC Smart-UPS SRT is easy to operate thanks to a tilting graphic LCD screen and physical buttons. This makes it possible to set and read the basic functionalities. Because the background color of the screen changes depending on the type of warning, the severity of the situation can be quickly visually assessed. Thanks to the included 4-post rail kit, you can easily mount the UPS in a rack.

Manage your Smart-UPS

Thanks to the pre-installed APC Network Management Card (AP9641), you can easily connect the APC UPS to the network. This way you can monitor and manage the UPS remotely (SNMP) and the UPS can send a shutdown signal to multiple physical and/or virtual servers using PowerChute Network Shutdown software.

PowerChute Network Shutdown

PowerChute Network Shutdown is UPS management software that works with the UPS Network Management Card to protect Windows, Linux and Host ESXi, as well as hyperconverged and virtual infrastructure*. In the event of a power outage, PowerChute can properly shut down your virtual machines and the preconfigured boot sequence ensures they are turned back on.

*An additional license is required for HCI and virtual machine support:
1 year: SWPCNS1Y-DIGI
3 years: SWPCNS3Y-DIGI
5 years: SWPCNS5Y-DIGI

Remote management and monitoring of your network

The network card can be managed remotely via the easy-to-use web browser interface, remote management software EcoStruxure™ IT (SFTWES1-DIGI) or other SNMP-compatible system. Tip EcoStruxure™ IT also includes the functionalities of the support contract below.

Support contract

The optional network card support contract license* ensures you are always up to date and secure and includes additional benefits such as frequent updates with:
• New and improved features
• Security updates
• Advanced support

*The above license is available in the variants:
1 year: SWNMC3SU-1Y-DIGI
3 years: SWNMC3SU-3Y-DIGI
5 years: SWNMC3SU-5Y-DIGI

Extend the lifespan

The internal battery cartridge (APCRBC152) can be replaced easily, safely and independently by the user. This without having to switch off the APC SRT3000RMXLI-NC or connected equipment. This way you can easily and cheaply extend the lifespan of the APC Smart-UPS and your equipment always remains online.

Warranty extension

The manufacturer's warranty of the SRT3000RMXLI-NC is 3 years, with the exception of the battery cartridge, which has a 2-year manufacturer's warranty. Both are extended by 3 years to 6 and 5 years respectively with the APC service pack (WBEXTWAR3YR-SP-04).

Switched Outlet Groups: Remote reboot and phased start-up

Thanks to the Switched Outlet Groups, it is possible to configure a phased/delayed power-on per UPS outlet group. This reduces the peak load on the UPS and brings it closer to the constant load, which limits oversizing of the UPS.

It is also possible to reset a group of multiple UPS outputs and the equipment connected to them. If a network card (ap9640) is used in combination with Ecostruxure IT Expert (SFTWES1-DIGI), this can even be done remotely.

You also cannot eliminate critical loads; This way you extend the runtime for critical equipment.

Green Premium

This label is Schneider Electric's commitment to products with best-in-class environmental performance. Green Premium promises to comply with the latest regulations, transparency on environmental effects and circular and low CO2 emission products.

Green Premium:
- Stands for an energy-efficient product that helps our customers achieve their CO2 reduction goals and save energy costs at the same time. The energy efficiency of this product is at least 10% higher than the market average.

- Provides insight into the environmental effects of the product, this data is available 24/7 via the digital product environmental profile, see https://checkaproduct.se.com/

- Commits to minimal use of hazardous substances within and beyond regulatory compliance (RoHS/REACh)

Included in the box
1x SRT3000RMXLI-NC
1x USB cable
1x C13 to C14 power cord 1.2M
1x Software CD with Powershute Network Shutdown Edition
1x Documentation CD
1x Schuko to C19 input power cord 2M
1x British BS1363A to C19 input power cord
1x C19 to C20 input power cord 2.5M
2x Rackmount mounting brackets

1x Temperature sensor

Techninė specifikacija

Savybės	
UPS topologija	Dviguba konversija (prisijungus)
Išvesties galia (VA)	3 kVA
Išvesties galia	2700 W
Signalų forma	Sinusas
Įvesties eksploatacinė įtampa (min.)	100 V
Įvesties eksploatacinė įtampa (maks.)	275 V
Įėjimo dažnis	40 - 70 Hz
Išvesties darbinė įtampa (min.)	220 V
Išvesties darbinė įtampa (maks.)	240 V
Išvesties dažnis	50/60 Hz
Automatinis įtampos reguliavimas (AVR)	Taip
Viršįtampio energijos įvertinimas	340 J
Efektyvumas	92%
Amplitudės koeficientas	3:1
Avarinis elektros išjungimas (EPO)	Taip
Išvesties įtampa THD	2%
Garso lygis	55 dB
Apsauga nuo viršįtampių	Taip
Maitinimo apsaugos ypatybės	Apsauga nuo perkrovos
Garsiniai perspėjimo signalai	Taip
Garsinio pavojaus signalo režimai	Baterijos keitimas
Automatinis paleidimas iš naujo	Taip
Ryšys	
AC išėjimo tipai	C13 šakotuvas, C19 šakotuvas
Maitinimo laido kištukas	C20 šakotuvas
USB prievadas	Taip
Nuoseklioji sąsaja	Taip
Nuosekliosios sąsajos tipas	RJ-45
„SmartSlot“	Taip
„SmartConnect“ prievadas	Ne

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Baterija	
Baterijos technologija	Rūgštinis akumuliatorius (VRLA)
Baterijos talpa	505 VAh
Tipiško laikino maitinimo trukmė pilna apkrova	4 min
Tipiško laikino maitinimo trukmė pusei apkrovimo	11,8 min
Baterijos veikimo trukmė (maks.)	5 metai
Baterijos įkrovimo laikas	3 h
Hot-Swap baterija	Taip
Automatinis baterijos bandymas	Taip
Aušinimo paleidimas	Taip
Konstrukcija	
Forma	Stelažas
Produkto spalva	Juoda
Rėmo pajėgumas	2U
Kabelio ilgis	2,44 m
Ekrano tipas	LCD
LED indikatoriai	Baterijos keitimas
Tarptautinės apsaugos (IP) kodas	IP20
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 40 °C
Sandėliavimo temperatūros norma (T-T)	-15 - 45 °C
Darbo santykinės drėgmės diapazonas	0 - 95%
Sandėliavimo santykinis drėgmės diapazonas	0 - 95%
Darbinis aukštis	0 - 3000 m
Ne darbinis aukštis	0 - 15000 m
Sertifikatai	
Atitikties sertifikatai	RoHS
Sertifikavimas	CE, VDE, RCM, EAC, IEC/EN 62040-1, IEC/EN 62040-2, UL-1778, FCC 15 A, CSA
Pakuotės turinys	
Pridedama valdymo kortelė	Taip
Greito diegimo vadovas	Taip
Tvarumas	
Tvarumo sertifikatai	Green Premium
Svoris ir matmenys	

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Plotis	432 mm
Ilgis	635 mm
Aukštis	85 mm
Svoris	31,3 kg
Pakuotės duomenys	
Pakuotės plotis	599 mm
Pakuotės gylis	871 mm
Pakuotės aukštis	246 mm
Paketo svoris	39,3 kg
Logistikos duomenys	
Gaminių skaičius ant padėklo	6 vnt
Darniosios sistemos (DS) kodas	85078000
Bendrasis anglies pėdsakas (kg of CO2e)	4988,41
Kitos savybės	
Išėjimo įtampa	230 V
Matmenys ir svoris	
Matmenys (I × P × A)	88,00cm × 61,00cm × 26,00cm

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE
rue Joseph Monier 35, 92500 Rueil Malmaison, FR
se.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt