Vertiv Geist MGU5MGW1-36CF13-3PS56B2A10-S-A power distribution unit (PDU) 36 AC outlet(s) 0U Black

Gamintojas: **VERTIV** · Modelis: **VP7G30AH** · Prekės kodas: **974568**



3 811,90 €

Kaina su PVM

Be PVM: **3 150,33 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Remotely reboot outlets to power cycle unresponsive IT equipment or increase runtime of critical equipment upon power failure with outlet-level control
- ✓ Reliable power distribution with local and remote outlet-level power monitoring options offer quick access to critical power usage information down to the device level to evaluate energy usage trends and maximize uptime
- ✓ Environmental monitoring capabilities with the addition of optional environmental sensors ensure users have critical infrastructure data at their fingertips to prevent climate-related equipment failure and system downtime
- ✓ Fault-Tolerant Daisy Chaining with RSTP simplifies intelligent rPDU connectivity and ensures data is reported even when a break in the network chain occurs. Supports up to 40 rPDUs
- ✓ Daisy-chain up to 50 devices on a single IP address and reduce deployment time with self-configuration of downstream devices

Aprašymas

Upgradeable Switched Outlet Level Monitored rPDUs provide reliable power distribution to critical IT equipment while delivering individual outlet level control and a comprehensive view of outlet level power usage via remote network access. Includes environmental monitoring capabilities to obtain real-time environmental metrics. With the PowerIT Upgradeable hot-swap technology, users may easily update the rPDU technology with the addition of the appropriate Interchangeable Monitoring Device (IMD) as business needs change.

Techninė specifikacija

Design

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

PDU types	Switched
Rack capacity	0U
Type	Three-phase
Mounting	Vertical
Product colour	Black
Display	LCD
On/off switch	No

Ports & interfaces

AC outlets quantity	36 AC outlet(s)
AC outlet types	C13 coupler, C19 coupler
Power plug	IEC 60309
Serial ports quantity	1
Ethernet LAN (RJ-45) ports	1
USB ports quantity	1

Features

Reset button	Yes
Cable length	3 m

Management features

Supported network protocols	DHCP, HTTP, HTTPS, IPv4, IPv6, LDAP, NTP, RADIUS, RSTP, SSH, SMTP, SNMP (v1/v2c/v3), Syslog, TACACS+, Modbus TCP

Power

Nominal input voltage	200-240 V
Maximum current	32 A
AC input frequency	50/60 Hz
Nominal output voltage	32 V
Load capacity	230 VA
Power protection features	Over current

Certificates

Certification	CE Marked UKCA Marked Complies with IEC 62368-1 (DOC Available) Complies with EN 55032 and EN 55035 RoHS Compliant $C_{\text{ρ}}$ Mark

Operational conditions

Operating temperature (T-T)	10 - 45 °C

Weight & dimensions

Width	51 mm
Depth	66 mm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Height	1829 mm
Packaging data	
Package weight	9.98 kg
Matmenys ir svoris	
Svoris	13,10kg

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

Vertiv

ATSAKINGAS ASMUO ES

Vertiv GmbH
August-Everding-Str 25, 81671 München, DE
vertiv.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt