WRL CAMERA PAN/TILT/DUAL TAPO C675D KIT TP-LINK

Gamintojas: **TP-LINK** · Modelis: **TAPO C675D KIT** · EAN: **8885020629903** · Prekės kodas: **974712**



215,90 €

Kaina su PVM

Be PVM: **178,43 €**

Sandėlyje


Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt











Aprašymas

TP-Link Tapo C675D KIT

The Big Picture and the Fine Details

See the whole scene and the action in one device.

Capture the Full Story in a Single Frame

See more of your property at a glance. The ultra-wide lens delivers expansive coverage with crisp clarity from corner to corner.

Stay Locked on the Action

The telephoto pan/tilt zoom lens follows movement with remarkable accuracy, capturing crisp close-up details like faces, license plates, and more.

Multiple Perspectives in One Device

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Mount it where coverage matters most and monitor driveways, yards, and key entry points with greater flexibility—reducing blind spots without adding extra cameras.

Auto Zoom Tracking
Instantly locks onto motion and zooms in with precision, capturing crystal-clear 4K detail without manual control.

Tap to Zoom In
Tap anywhere in the scene to instantly zoom in and view sharp 4K close-ups exactly where you want to focus.

Synchronized Smart Tracking
Dual-lens synchronized tracking keeps both views actively following movement, maintaining full-scene context and detailed close-ups at the same time.

See Every Detail in True 4K Clarity
Dual 4K lenses capture every detail with exceptional clarity. From wide scenes to close-up moments, everything is recorded in true 4K resolution.

Sharp, Vivid Color at Night
Starlight Color Night Vision with built-in spotlights for vivid nighttime detail, plus IR mode for clear visbility in total darkness.

24/7 Continuous Capture
Capture all activity day and night, not just when motion is detected.

Farther Detection. Faster Alerts. No Missed Motion.
When 24/7 monitoring is enabled, the extended 60 ft detection range and smarter motion sensing means quicker alerts and no missed activity.

Built-In Solar Power, Fully Wire-Free
Place your camera anywhere without needing an outlet. With just 90 minutes of direct sunlight, the integrated solar panel supports daily operation, reducing the need for manual recharging. The built-in battery ensures reliable performance even during cloudy days.

Rapid Alerts. Instant Deterrence.
When alarm mode is active, detected activity triggers red-and-blue flashing lights and a built-in siren to deter intruders, while sending an instant notification to your phone.

Reliable Protection in Any Weather
IP65-rated protection keeps Tapo C675D KIT performing in rain, dust, and extreme temperatures, providing steady, year-round security without needing an outlet.

Secure Ways to Secure Your Footage
Local MicroSD Storage
Store footage directly on a microSD card up to 512GB (sold separately) for private and reliable access. No subscription or internet connection required.

Tapo Care Cloud Storage
Receive notifications with detection snapshots, encrypted protection, data backups, and up to 30 days of video history with Tapo Care cloud services (subscription required).

Unified Video Management
Tapo H500 and H200 (sold separately) offer a simple, centralized way to view and store clips from your entire Tapo camera network. Manage and review footage from all your devices in one place for easier security control.

Stay Connected, Clearly, and Seamlessly

Two-Way Audio Noise Reduction

Hear and speak clearly through your Tapo camera with built-in noise reduction. Whether you're greeting a visitor or calming your pet, every word comes through crisp and clear.

Smart Integration

Control your camera hands-free with Alexa and Google Assistant. View live feeds, manage alerts, or automate routines.

Dual-band Wi-Fi (2.4G/5GHz)

Connect the camera to 5 GHz for faster speed or 2.4 GHz for longer range. Enjoy more stable connectivity for lag-free Dual 4K live viewing.

- Reduce Blind Spots - A fixed wide-angle lens captures the full scene at all times, while the pan/tilt lens roams 360° horizontally to track and zoom in on activity in another area. Two perspectives, one device
- Lens 1: 169° Ultra-Wide Coverage - See more of your property at once with an expansive 169° field of view, keeping your front yard, back patio, and more in frame at all times
- Lens 2: 360° Auto-Tracking with Zoom - When motion is detected in the wide view, this lens instantly locks on and tracks the subject across 360°, keeping critical details in sharp focus as the action unfolds
- Set It Up Once. The Sun Handles the Rest - Just 90 minutes of sunlight recharges the camera for continuous power. The battery holds up to 3 months per charge, keeping your camera running through extended cloudy periods
- Vivid Color Even After Dark - Starlight color night vision delivers brighter, more detailed low-light imagery so facial features and vehicle details stay clearly visible after sunset
- Detect People, Vehicles & Pets Without a Subscription - On-device AI accurately identifies people, vehicles, and pets in real time, cutting down on false alerts and unnecessary notifications. No monthly fee required
- 24/7 Continuous Capture - Never wonder what happened between motion alerts. Captures images at customizable 1–60 second intervals, with AI-extended detection reaching up to 60 ft beyond traditional PIR sensors
- Dual-Band Wi-Fi Connectivity - Supports both 5 GHz and 2.4 GHz Wi-Fi bands. Use 5 GHz for faster speeds closer to your router, or 2.4 GHz for broader range across your property
- Built to Last with Smart Deterrence - IP65-rated stands up to rain, dust, and snow for reliable year-round performance. Built-in red and blue warning lights and a siren actively deter intruders the moment motion is detected

Summary: TP-Link Tapo C675D KIT. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wireless. Mounting type: Ceiling/Wall/Pole, Product colour: White, Protection features: Rain proof, Dust resistant, Temperature proof. Lens viewing angle, horizontal: 140.8°, Lens viewing angle, vertical: 74.7°, Lens viewing angle, diagonal: 169.7°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Digital zoom: 18x | Vendor Homepage: https://www.tp-link.com/en/home-networking/cloud-camera/tapo-c675d-kit/ | Tipas: IP apsaugos kamera | Ryšio technologija: Bevielis | Talpinimas palaikomas: Lauke | Virtualus asistentas: Amazon Alexa & Google Assistant | Dienos / nakties režimas: Taip | Montavimo tipas: Ant lubų / sienos / stulpo | Produkto spalva: Balta | LED indikatoriai: Taip | Apsaugos ypatybės: Atsparios lietui/Atsparus dulkėms/Atsparus temperatūrai | Tarptautinės apsaugos (IP) kodas: IP65 | Neperpučiamas: Taip | Kameros panoramavimo valdymas: Taip | Kameros pakėlimo valdymas: Taip | Objektyvo vaizdo kampas, horizontalus: 140.8 | Objektyvo vaizdo kampas, vertikalus: 74.7 | Objektyvo vaizdo kampas, įstrižainė: 169.7 | Lęšio matymo kampas, horizontalus (antroji kamera): 57.3 | Lęšio matymo kampas, įstrižas (antroji kamera): 66.5 | Lęšio matymo kampas, vertikalus (antroji kamera): 31 | Posvyrio kampo intervalas: 0 - 128 | Viso diapozonas: 0 - 360 | Optinio sensoriaus dydis: 1/2.7 | Jutiklio tipas: CMOS | Priartinimo galimybė: Taip | Skaitmeninis priartinimas: 18 | Lęšių skaičius: 2 | Maksimalus apertūros skaičius: 1.6 | Naktinis matymas: Taip | Naktinio matymo atstumas: 15 | Spalvoto naktinio matymo nuotolis: 16 | LED tipas: IR | Infraraudonųjų spindulių bangos ilgis: 850 | Maksimali rezoliucija: 3840 x 2160 | Vaizdo įrašymas: Taip | Kadrų sparta: 15 | Įmontuoti garsiakalbiai: Taip | Audio sistema: 2 krypčių | Įmontuotas mikrofonas: Taip | Ethernet LAN jungtis: Ne | Palaikomi tinklo protokolai: TCP/IP, DHCP, ICMP, DNS, NTP, HTTPS, TCP, UDP | „Wi-Fi“: Taip | Wi-Fi standartai: 802.11a/802.11b/802.11g/Wi-Fi 4 (802.11n) | Bluetooth: Ne | Integruotas kietasis diskas: Ne | Integruotas kortelių skaitytuvas: Taip | Suderinamos atminties kortelės: MicroSD (TransFlash) | Maksimalus atminties kortelės dydis: 512 | DC įėjimo lizdas: Taip | Įmontuota sirena: Taip | Sirenos triukšmo lygis: 87.1 | Apsaugos algoritmų palaikymas: 128-bit AES/WPA2-PSK/WPA3-PSK/WPA-PSK | Įspėjamojo pranešimo tipas: Push notification,Snapshot alert message | Judesių jutiklio technologija: Pasyvus infraraudonųjų spindulių jutiklis (PIR) | Judesių jutiklis: Taip | Pažangios vaizdo stebėjimo (IVS) sistemos savybės: Naminių gyvūnų aptikimas/Transporto priemonių aptikimas/Žmonių aptikimas | Vaizdo judesio detekcija: Taip | Išmaniojo telefono nuotolinio valdymo palaikymas: Taip | Valdymo programinė įranga: Tapo App | Maitinimo šaltinio tipas: Solar,DC | DC išeigos įtampa: 5 | Baterijos technologija: Ličio-jonų (Li-Ion) | Perkraunama baterija: Taip | Darbo temperatūros diapazonas (TT): -20 - 45 | Sandėliavimo temperatūros norma (T-T): -40 - 60 | Darbo santykinės drėgmės diapazonas: 10 - 90 | Sandėliavimo santykinis drėgmės diapazonas: 0 - 90 | Palaikomos mobiliosios operacinės sistemos: Android 10.0/Android 11.0/Android 12.0/Android 13.0/Android 14.0/Android 15/Android 16/Android

7.0/Android 7.1/Android 7.1.2/Android 8.0/Android 8.1/Android 9.0/iOS 12/iOS 12.4/iOS 13/iOS 13.4/iOS 14/iOS 14.3/iOS 14.5/iOS 15/iOS 16/iOS 17/iOS 18/iOS 26 | Plotis: 102.2 | Ilgis: 160.3 | Aukštis: 132 | Kabelio ilgis: 0.5 | Atitikties sertifikatai: CE/Federalinė ryšių komisija (FCC)/JRF/KC/RCM/VCCI | Fotoaparatų skaičius: 1 | Pridėti kabeliai: USB | Pridėti sraigtai: Taip | Pridedami pritvirtinimai: Taip | Greitos pradžios vadovas: Taip | Tvirtinimo šablonas: Taip | Aplinkos šviesos jutiklis: Taip | Bruto svoris: 1.88 | Neto svoris: 1.5 | Vienetų skaičius vienoje siuntimo dėžėje: 4 | Vieneto plotis: 27.5 | Vienetų skaičius ant paletės: 0 | Shipping Box Height: 27.5 | Vieneto gylis: 22 | Vieneto aukštis: 12.5 | Name: WRL CAMERA PAN/TILT/DUAL TAPO C675D KIT TP-LINK | Model: TP-Link Tapo C675D KIT | Model name: Tapo C675D KIT

Techninė specifikacija

Matmenys ir svoris	
Matmenys (I × P × A)	22,00cm × 28,00cm × 13,00cm