# Intellinet 791298 keystone module

Gamintojas: **INTELLINET** · Modelis: **791298** · EAN: **766623791298** · Prekės kodas: **976815**




**3,90 €**

Kaina su PVM

Be PVM: **3,22 €**

**Sandėlyje**

**Prekė internetu**

Nuskenuokite kodą arba apsilankykite www.shopro.lt

## Pagrindinės savybės

- ✓ For easy, time-saving and tool-free deployment in blank patch panels, wall plates or surface connection boxes
- ✓ Slimline design, only 14.8 mm (0.58 in.) wide for comfortable side-by-side installation
- ✓ Cat6a Class EA RJ45 module with 10G and 500 MHz in accordance with ISO/IEC 11801
- ✓ STP 360° shielded RJ45 module for PoE applications up to IEEE802.3bt / PoE++ / 4PPoE / Ultra PoE
- ✓ 6 micro-inch gold-plated contacts
- ✓ Supports solid wire with 22/1 to 26/1 AWG
- ✓ Standard 8P8C design, compatible with all network RJ45 connections
- ✓ Compatible and color-coded with T568A and T568B
- ✓ Fully backward compatible with all the previous cable categories, including Category 6, 5e and 5
- ✓ Cable tie included
















## Aprašymas

The Cat6a 10G Shielded Toolless Slim Keystone Jack, Black from Intellinet Network Solutions is designed for quick, seamless side-by-side deployment. Without any special tools, this module easily snaps into blank patch panels, wall plates or surface connection boxes. It is suitable for solid conductor cables in high-performance network applications up to 10GBase-T and PoE applications up to IEEE802.3bt / PoE++ / 4PPoE / Ultra PoE. For maximum signal integrity, it is equipped with gold-plated contacts and 360° STP shielding.

## Techninė specifikacija

| | |
|---|---|
| **Features** | |
| Construction type | Flat |
| Product colour | Black, Stainless steel |
| Connector 1 | RJ-45 |
| Connector 1 gender | Female |
| Cabling technology | 10GBase-T |
| Connector contacts plating | Gold |
| Cable types supported | Cat6a |
| Plug/connector retention force | 30 N |
| Housing material | Zinc |
| Networking standards | IEEE 802.3bt |
| Frequency | 500 MHz |
| Power over Ethernet (PoE) | Yes |
| **Operational conditions** | |
| Operating temperature (T-T) | -10 - 60 °C |
| Storage temperature (T-T) | -40 - 70 °C |
| Operating relative humidity (H-H) | 10 - 90% |
| **Technical details** | |
| Compliance certificates | CE, REACH, RoHS, UKCA |
| **Weight & dimensions** | |
| Width | 14.8 mm |
| Depth | 36 mm |
| Height | 20 mm |
| Weight | 10 g |
| **Packaging data** | |
| Package weight | 20 g |
| **Packaging content** | |
| Quantity per pack | 1 pc(s) |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

## Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas
- Atitikties deklaracija

## Gamintojo ir saugos informacija

GAMINTOJAS

**IC Intracom Vertriebs GmbH**
Löhbacher Str. 7, D-58553 Halver, DE
intellinetnetwork.eu

PLATINTOJAS

**MB KOMPIUTERIŲ GURU**
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

### Saugos dokumentai

- Atitikties deklaracija

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.