Axagon ADE-TXCA USB-C + USB-A 3.2 Gen 1 - Gigabit Ethernet adapter, Asix AX88179

Gamintojas: **AXAGON** · Modelis: **ADE-TXCA** · EAN: **8595247907943** · Prekės kodas: **977184**



18.90€

Kaina su PVM

Be PVM: **15.62€**

In Stock

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wired
- ✓ USB Type-A/USB Type-C 2.0/3.2 Gen 1 (3.1 Gen 1) Ethernet
- ✓ Fast Ethernet, Gigabit Ethernet 1000 Mbit/s 10/100/1000BaseT(X)
- ✓ Component for: PC/Laptop Chipset: ASIX AX88179










Aprašymas

The external network card AXAGON ADE-TXCA easily converts USB-C or USB-A 3.2 Gen 1 port to Gigabit Ethernet port. Thanks to the cable with USB-C connector, on which the USB-C -> USB-A reduction is attached, you can connect the Ethernet adapter to any computer, tablet or phone. USB network adapter compatible with 10/100/1000 Mbit/s expands the computer with a fast and stable network connection, adds the missing RJ-45 network connector, adds another network card, or replaces the original non-functional network connection.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

In addition to gigabit throughput, the LAN adapter offers a wide range of features such as IPv4/IPv6 checksum to reduce CPU load by checksums, the crossover detection and auto-correction, TCP large send offload, support for various modes of the Wake-on-LAN feature, the work with VLAN and advanced Power Management features.

The metal adapter cover is made of aluminum and provides perfect mechanical protection and excellent heat dissipation. Due to its minimal dimensions and weight, it is an ideal accessory for laptops and other mobile devices. The support for current versions of Windows, macOS, and Linux, Chrome or Android operating systems allows it to be used for any desktop, laptop or ultrabook equipped with a modern double-sided USB Type C connector or a classic USB-A connector. In Windows from version 8.1 and above, the adapter enables easy automatic installation without the need for an Internet connection. The Ethernet adapter will also be used by users of tablets or mobile phones supporting the possibility of a wired Ethernet connection. In addition, thanks to the chip used, the adapter is also supported by the operating system of Nintendo Switch game consoles.

Input:
• USB 5Gbps (USB 3.2 Gen 1 / USB 3.0).
• Backward compatible with USB 480Mbps (USB 2.0) and USB 1.1.
• Compatible with Thunderbolt 3 and 4.
• Connection to a computer, mobile phone or tablet via a USB-C male connector or with a connected adapter via a USB-A male connector.

Output:
• Gigabit Ethernet interface with RJ-45 connector for UTP or STP cable connection.
• Supported transmission rates for the Ethernet interface 10/100/1000 Mb/s.
• Supported IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T specifications.
• 10/100/1000 Mb/s auto-detection.
• Supports IPv4 / IPv6 packet Checksum Offload Engine (COE) to reduce processor load, including IPv4 IP/TCP/UDP/ICMP/ IGMP & IPv6 TCP/UDP/ICMPv6 checksum control and generation.
• Supports TCP Large Send Offload V1 and V2.
• Supports IEEE 802.1P Layer 2 priority encoding & decoding.
• Supports IEEE 802.1Q VLAN tagging.
• Supports IEEE 802.3az EEE (Energy Efficient Ethernet) - reduce power consumption at rest.
• Supports Jumbo frame.
• Supports Auto MDI/MDIX - crossover detection and auto-correction eliminates the need for crossover cables.

Other features:
• Full Plug and Play and Hot Plug support.
• Supports CDC-ECM – for automatic installation of drivers across different OSs.
• CDC-NCM support - for native support without driver installation in iOS/iPadOS/macOS/Linux.
• Adapter power supply via USB (bus power) - no auxiliary power supply required.
• Two LEDs to indicate network activity and the adapter's connection to the network.
• Dimensions 76 x 24 x 16 mm.
• Weight 34 g (incl. cable and reduction).
• USB cable length 15 cm.
• ASIX AX88179A chipset is used.

Wake-on-LAN feature support in different modes:
• Supports sleep mode and remote Wake Up via Magic Packet, Microsoft Wakeup Frame and Link Change Wake-up.
• Supports Bonjour wake-on-demand.
• Supports Wakeup Packet Indication.
• Supports Microsoft Modern Standby.
• Advanced Power Management features:
• The adapter supports advanced power management to reduce losses during standby or light traffic on the network. It further supports advanced power saving when the Ethernet cable has been disconnected.
• Supports Power Management offload (ARP & NS).

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

• Supports ECMA-393 proxZzzy® standard for sleeping hosts to manage the network connection of sleeping guests using proxy servers.

Supported operating systems:
• Windows, macOS, iPadOS, iOS, Linux, Chrome OS, Nintendo Switch system software and Android (WARNING - check with the Android device manufacturer if the Ethernet connection is supported).

Package contains:
• USB - Gigabit Ethernet adapter with fixed 15 cm long USB-C cable and USB-C / USB-A reduction,
• multilingual manual CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / SK / SWE / TR / UA / BG / CN / ARA,
• packed in a cardboard box with a hanging hole.

Techninė specifikacija

Ports & interfaces	
Connectivity technology	Wired
Host interface	USB Type-A/USB Type-C
Interface	Ethernet
Ethernet LAN (RJ-45) ports	1
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)
Network	
Maximum data transfer rate	1000 Mbit/s
Networking standards	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u
Ethernet LAN	Yes
Ethernet interface type	Fast Ethernet, Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Cabling technology	10/100/1000BaseT(X)
Wake-on-LAN ready	Yes
Full duplex	Yes
Jumbo frames support	Yes
LAN controller	ASIX AX88179
Design	
Internal	No
Component for	PC/Laptop
Product colour	Grey
Chipset	ASIX AX88179
Plug and Play	Yes
LED indicators	Yes
Country of origin	China
Certification	CE, RoHS

Power	
USB powered	Yes
System requirements	
Windows operating systems supported	Yes
Mac operating systems supported	Yes
Linux operating systems supported	Yes
Server operating systems supported	Yes
Weight & dimensions	
Width	76 mm
Depth	24 mm
Height	16 mm
Weight	34 g
Packaging data	
Package width	203 mm
Package depth	99 mm
Package height	28 mm
Package weight	78 g
Packaging content	
Cables included	USB, USB Type-A to USB Type-C
Manual	Yes
Technical details	
Warranty period	2 year(s)
Compliance certificates	RoHS, CE
Matmenys ir svoris	
Matmenys (I × P × A)	3.00cm × 10.00cm × 20.00cm

Dokumentai ir vaizdo įrašai

› User manual

Gamintojo ir saugos informacija

MANUFACTURER

RealQ, s.r.o.
Železná 663/5, 619 00 Brno-jih, CZ
axagon.eu

DISTRIBUTOR

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.