Axagon PCEU-232RS PCIe controller 2x ext. + 2x int. USB 5Gbps

Gamintojas: **AXAGON** · Modelis: **PCEU-232RS** · EAN: **8595247908599** · Prekės kodas: **977185**



15.90€

Kaina su PVM

Be PVM: **13.14€**

In Stock

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Internal
- ✓ Host interface: PCIe
- ✓ Output interface: USB 3.2 Gen 1 (3.1 Gen 1)
- ✓ 5 Gbit/s







Aprašymas

The AXAGON PCEU-232RS PCI-Express card adds four USB 5Gbps ports to your desktop computer. The card is designed for fast data transfers at speed up to 5 Gb/s.

Two USB-A ports are taken out to the bracket. You can connect two different USB devices such as printers, keyboards, card readers, flash drives, external HDDs, etc. Another two ports (in the form of an internal USB 5Gbps 19pin connector) are integrated on the card board. This allows connection of an internal USB reader or connection of the front USB ports of a PC case.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Reliable power supply of the card is provided from the computer power supply via the SATA power connector. The USB controller is equipped with a renowned Renesas company chipset with proven seamless compatibility and UASP support.

The package contains a low-profile bracket for mounting the adapter into low profile cases.

Input:
• PCI-Express 2.0 interface, compatible with PCI-Express 1.0a / 1.1 / 2.1. / 3.0 / 4.0.
• Number of 1-Lane lines (x1), compatible with x1 / x4 / x8 / x16 PCIe slots.
• A bandwidth of 1-Lane PCI-Express 2.0 bus up to 5 Gb/s.

Input (power supply):
• SATA 15-pin male power connector.

Output:
• 2x external USB 5Gbps port with USB A-F connectors.
• 19-pin internal USB 5Gbps connector with two ports used for example to connect an internal USB reader or the front USB ports of a PC case.
• USB - USB 5Gbps interface - before USB 3.2 Gen 1 / USB 3.0.
• Compatible with USB 3.2 Gen 2, backward compatible with USB 2.0 and USB 1.1.
• Supports transmission rates 5000 / 480 / 12 / 1.5 Mb/s.
• When connected to a PCI-Express bus version 1.0, theor. transmission rate max. 2500 Mb/s.

Other features:
• Full Plug and Play support.
• Supports concurrent activity of SuperSpeed USB, USB 2.0 and USB 1.1 devices.
• Compliant with the final official xHCI specification revision 1.0 by USB-IF.
• Supports UASP (USB Attached SCSI) for faster data transmission in Windows 8 and later.
• Fully supports Hot Plug connecting and disconnecting of USB devices while running.
• Internal SATA power connector for powering the controller from the PC power supply.
• Renesas PD720201 chipset is used.

Supported operating systems:
• MS Windows XP / Vista / 7 / 8 / 8.1 / 10 / 11 and later, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 / 2022 (supported are all 32- and 64-bit Windows OS versions), Linux with kernel 2.6.31 and above.
• Note: Drivers are only installed for Windows XP / Vista / 7. For Linux, Windows 8 / 8.1 / 10 / 11, Server 2012 / 2016 / 2019 / 2022 and later versions, no external drivers are required, they are already part of the operating system.

Package contains:
• PCI-Express card with a standard bracket,
• low profile bracket,
• multilingual manual CZ / DE / DK / ENG / ESP / EST / FIN / FR / GR / HR / HU / IT / LT / LV / NL / NOR / PL / PT / RO / SK / SLO / SRB / SWE / TR / UA / ALB / BG / BOS / CN / ARA,
• packed in a cardboard box.

Techninė specifikacija

Ports & interfaces	
Host interface	PCIe
Output interface	USB 3.2 Gen 1 (3.1 Gen 1)
Expansion card form factor	Full-height / Low-profile

Expansion card standard	PCIe 2.0
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
SATA power connector type	SATA 15-pin
Internal USB 3.2 Gen 1 (3.1 Gen 1) ports quantity	2
Design	
Internal	Yes
Hot-Plug support	Yes
Easy to install	Yes
Country of origin	China
Certification	CE, RoHS
Features	
Data transfer rate (max)	5 Gbit/s
Plug and Play	Yes
System requirements	
Windows operating systems supported	Yes
Linux operating systems supported	Yes
Server operating systems supported	Yes
Technical details	
Warranty period	2 year(s)
Compliance certificates	RoHS, CE
Packaging data	
Quantity per pack	1 pc(s)
Manual	Yes
Package width	110 mm
Package depth	145 mm
Package height	25 mm
Package weight	77 g
Package type	Box
Matmenys ir svoris	
Matmenys (I × P × A)	3.00cm × 11.00cm × 15.00cm

Dokumentai ir vaizdo įrašai

› User manual

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Gamintojo ir saugos informacija

MANUFACTURER

RealQ, s.r.o.
Železná 663/5, 619 00 Brno-jih, CZ
axagon.eu

DISTRIBUTOR

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt