Salicru SPS 1000 ADV T

Gamintojas: **SALICRU** · Modelis: **6A0EA000002** · EAN: **8436035923717** · Prekės kodas: **977256**



352.90€

Kaina su PVM

Be PVM: **291.65€**

In Stock

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-interactive technology with sine-wave output
- ✓ Permanent AVR stabilisation (buck-boost)
- ✓ Compact tower format
- ✓ RS-232 and USB-HID communication interfaces
- ✓ Monitoring and management software for Windows, Linux and Mac
- ✓ Smart slot for SNMP adapter
- ✓ Compatible with APFC power supplies
- ✓ Possibility of backup extension
- ✓ (1) Complete display showing all operating information
- ✓ IEC output sockets






Aprašymas

Salicru's SPS ADVANCE T series offers, as a UPS solution, optimum levels of efficiency and reliability for all critical devices that require power supply continuity and dependability. They come in a very compact tower format to save space in server and computer rooms. They also feature line-interactive technology to combat any fluctuations in the mains supply together with an output voltage that is always sine-wave, the highest quality possible to power all sensitive loads. For easier and more convenient use, they feature a display that shows all necessary information on the operation of the device and power supply (input/output voltage, % load, % battery, etc.) and a wide range of communication options through the USB interface with HID protocol, monitoring and management software (downloadable) and integrated smart slot (SNMP). Also noteworthy is their compatibility with current APFC (active power factor correction) power supplies. The power range for the SPS ADVANCE T series is: 850, 1,000, 1,500, 2,000 and 3,000 VA.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Techninė specifikacija

Features	
UPS topology	Line-Interactive
Output power capacity	1 kVA
Output power	700 W
Waveform	Pure sine
Input operation voltage (min)	165 V
Input operation voltage (max)	290 V
Input frequency	50/60 Hz
Output operation voltage (max)	230 V
Output frequency	50/60 Hz
Output frequency regulation	1 Hz
Output voltage regulation	10%
Automatic Voltage Regulation (AVR)	Yes
Efficiency	98%
Efficiency (Stabiliser mode (AVR))	92%
Efficiency (Battery mode)	80%
Emergency Power Off (EPO)	Yes
Overload capacity - line mode (1 minute)	110%
Overload capacity - battery mode (1 minute)	110%
Output voltage Total Harmonic Distortion (THD)	5%
Noise level	45 dB
Surge protection	Yes
Power protection features	Overdischarge, Overload, Short circuit
Audible alarm(s)	Yes
Audible alarm modes	Fault, Low battery alarm, Overload alarm
Maintenance-free	Yes
Ports & interfaces	
AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	6 AC outlet(s)
Number of output IEC jumpers	6
USB port	Yes
USB 2.0 ports quantity	1

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Serial interface	Yes
Serial interface type	RS-232
RS-232 ports	1
Emergency Power Off (EPO) connector	Yes
SmartSlot	Yes

Battery

Battery technology	Lead-Calcium (Pb-Ca)
Battery recharge time(90%)	4 h
Automatic battery test	Yes
Cold start	Yes

Design

Form factor	Tower
Product colour	Black
Cooling type	Active
Built-in fan	Yes
Display type	LCD
LED indicators	Yes

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	0 - 95%
Operating altitude	0 - 2400 m

Certificates

Certification	EN 62040-2, EN 62040-3, ISO-9001, ISO-14001

Safety regulation & standards

Safety	EN 62040-1

Weight & dimensions

Width	140 mm
Depth	327 mm
Height	191 mm
Weight	11.4 kg

Logistics data

Harmonized System (HS) code	85078000

Other features

Battery type	AGM

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Compatible operating systems	Windows, Linux, Mac
Output voltage	230 V

Dokumentai ir vaizdo įrašai

- User manual
- Product leaflet
- Vaizdo įrašas 1 objects.icecat.biz/objects/47182815_22907989.mp4
- Vaizdo įrašas 2 objects.icecat.biz/objects/47182815_18745823.mp4

Gamintojo ir saugos informacija

MANUFACTURER

Salicru S.A.
Avda de la Serra 100, 8460 Palautordera (Barcelona), ES
salicru.com

DISTRIBUTOR

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.