Intellinet 5-Port Gigabit Switch with PoE Passthrough, One IEEE 802.3bt (PoE++ / 4PPoE) PD PoE Port with 95 W Power Input, Four PSE PoE ports, PoE Power Budget up to 65 W, IEEE 802.3at/af Compliant Output, Desktop, Wall-mount Option

Gamintojas: **INTELLINET** · Modelis: **561808** · EAN: **766623561808** · Prekės kodas: **977638**



79.90€

Kaina su PVM

Be PVM: **66.03€**

In Stock

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Supports up to 95 W power input from a PoE injector or switch
- ✓ PoE power budget up to 65 watts when using AC power or IEEE 802.3bt via PD input port
- ✓ Provides up to four PoE network devices with power and data
- ✓ Doubles the connection distance between PoE source and device from 100 m (328 ft.) to 200 m (656 ft.)
- ✓ Can be powered via PoE or the included power adapter
- ✓ PoE power budget of 25 W through IEEE 802.3at connection and 10 W through IEEE 802.3af connection
- ✓ IEEE 802.3at/af-compliant RJ45 PoE/PoE+ output ports
- ✓ Power output up to 30 watts per port
- ✓ Saves installation costs by delivering data and power over existing network cables
- ✓ Supports IEEE 802.3at and IEEE 802.3af-compliant PoE devices (e.g., wireless access points, VoIP phones, IP cameras)






Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903



Aprašymas

Get the most out each Power over Ethernet connection with this PoE passthrough switch

The PoE-Powered 5-Port Gigabit Switch with PoE Passthrough from Intellinet Network Solutions is designed to take power from a PoE switch or injector and pass both data and electrical power to a number of PoE-compatible devices via standard Cat5e or Cat6 network cables. Equipped with five Gigabit Ethernet ports, this switch can power up to four wireless LAN access points and bridges, VoIP phones or IP video cameras, draw its own power from the PoE switch it is connected to, and deliver network speeds of up to 1,000 Mbps.

Usable as a PoE extender

Thanks to its PoE passthrough technology that extends a PoE connection, this versatile unit doubles the range between PoE source and device from 100 m (328 ft.) to 200 m (656 ft.). Using it this way also eliminates the time and expense of electrical rewiring, which ultimately minimizes the unsightly clutter of power cables in awkward places such as ceilings and walls while providing up to 30 W to compatible devices.

Power over Ethernet 802.3bt Compliant

This switch supports the IEEE 802.3bt protocol over four pairs (4PPoE), which allows for a power input up to 95 W. It forwards data at Gigabit speeds and offers up to 30 watts per port to a connected IEEE 802.3at- or IEEE 802.3af-compliant device.

The Perfect Workgroup Switch

When you connect the PD port (port 5) to a PoE injector or switch, this product uses some of the electric current to power itself and passes the available surplus power to up to four PoE edge devices, such as VoIP phones, allowing you to realize the full potential of each of the PSE ports in your data center.

Eliminate Bottlenecks with Gigabit Speeds

Equipped with five auto-sensing 10/100/1000 Mbps RJ45 Gigabit Ethernet ports, the 10 Gbps switch fabric provides plenty of performance for your computers and other networking devices.

Wall-mount option

For full installation flexibility, you can mount the switch on the wall through its four built-in holes or use the included non-slip rubber feet to place it on a desktop.

Techninė specifikacija

Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	5
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)

Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Cable types supported	Cat3, Cat5, Cat5e
Full duplex	Yes
Flow control support	Yes
Data transmission	
MAC address table	2048 entries
Switching capacity	10 Gbit/s
Store-and-forward	Yes
Jumbo frames support	Yes
Packet forwarding rate (1 Gbps)	1488000 pps
Packet forwarding rate (100 Mbps)	148800 pps
Packet forwarding rate (10 Mbps)	14880 pps
Packet buffer memory	1 MB
Design	
Housing material	Metal
LED indicators	Activity, Link, PoE, Power
Wall mountable	Yes
Power	
Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (max)	72 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Total Power over Ethernet (PoE) budget	65 W
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	0 - 70 °C

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Operating relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width	168 mm
Depth	93 mm
Height	32 mm
Weight	400 g
Packaging content	
Cables included	AC
Manual	Yes
Packaging data	
Package weight	900 g
Certificates	
Compliance certificates	CE, RoHS, Federal Communications Commission (FCC)
Certification	FCC Class A, CE, RoHS, UKCA, NDAA

Dokumentai ir vaizdo įrašai

- User manual
- Product leaflet

Gamintojo ir saugos informacija

MANUFACTURER

IC Intracom Vertriebs GmbH
Löhbacher Str. 7, D-58553 Halver, DE
intellinetnetwork.eu

DISTRIBUTOR

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt