Axagon PCEE-GRF tinklo plokštė Vidinis Eternetas 1000 Mbit/ai

Gamintojas: **AXAGON** · Modelis: **PCEE-GRF** · EAN: **8595247906120** · Prekės kodas: **978048**



11,89 €

Kaina su PVM

Be PVM: **9,83 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Vielinis
- ✓ PCI Express 1.1 Eternetas
- ✓ Gigabitinis eternetas 1000 Mbit/ai 10/100/1000BaseT(X)
- ✓ Vidinis Taikoma: PC Lustų rinkinys: Realtek RTL8111











Aprašymas

AXAGON PCEE-GRF PCI-Express network card adds high speed Gigabit Ethernet connection to your desktop computer. It enables a transmission speed of 10/100/1000 Mbit/s.

The network card is equipped with proven Realtek 8111 chipset. It ensures seamless compatibility with most operating systems.

Gigabit network card connects the computer to the Internet or a computer network, adds the missing RJ-45 connector, add another network card or replaces the original defunct network connection.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

In addition to an adapter with a standard size bracket, the package also includes a low profile bracket which allows the mounting into low profile cases.

Input:
• PCI-Express 1.1 interface, PCI-Express 1.0a / 2.0 / 2.1 / 3.0 compatible.
• Number of lines 1-Lane (x1), compatible with x1 / x4 / x8 / x16 PCIe slots.
• A bandwidth of 1-Lane PCI-Express 1.1 bus 2.5 Gb/s.

Output:
• Gigabit Ethernet interface with RJ-45 connector for UTP or STP cable connection.
• Supported transmission rates for the Ethernet interface 10/100/1000 Mb/s.
• Supported IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T specifications.

Other features:
• Full Plug and Play support.
• 10/100/1000 Mbit/s auto-detection.
• Supports Microsoft NDIS5, NDIS6 Checksum Offload (IPv4, IPv6, TCP, UDP) to reduce processor load.
• Supports Segmentation Task-offload (Large send v1 a Large send v2).
• Supports full-duplex transmission s IEEE 802.3x flow control.
• Supports IEEE 802.1P Layer 2 priority encoding.
• Supports IEEE 802.1Q VLAN tagging.
• Supports IEEE 802.3az-2010 (EEE) Energy Efficient Ethernet - reduce power consumption at standby.
• Supports Auto MDI/MDIX - crossover detection and auto-correction eliminate the need for crossover cables.
• Supports hardware ECC (Error Correction Code), CRC (Cyclic Redundancy Check) function.
• Supports Pair Swap/Polarity/Skew Correction.
• Two LEDs for indicating network activity and connection.
• The Realtek RTL8111E/F chipset is used.

Wake-on-LAN support in various modes:
• Supports sleep mode and remote wake up via AMD Magic packet, Microsoft Wakeup Frame, Microsoft Wake Packet Detection and also Link Change wake-up.
• Supports ECMA-393 proxZzzy® standard for sleeping hosts to manage the network connection of sleeping guests using proxy servers.

Advanced Power Management features:
The network card supports advanced power management to reduce losses during standby. It also supports advanced power saving when the Ethernet cable has been disconnected.
• Supports Advanced Configuration Power management Interface (ACPI).
• Supports Power Management offload (ARP & NS).
• Supports PCI MSI (Message Signaled Interrupt) and MSI-X.

Supported operating systems:
MS Windows XP / Vista / 7 / 8 / 8.1 / 10 / 11 and later, Windows Server 2003 / 2008 / 2012 / 2016 and later (supported are all 32- and 64-bit versions of OS Windows), MS DOS, MacOS X 10.4.x and higher, Linux kernel 2.4.x / 2.6.x / 3.x / 4.x, FreeBSD 7.x / 8.0 / 9.0, SCO Unix 5.0.6 / 5.0.7, SCO OpenServer 6, UnixWare 7.1.x, Novell server OS 5.x / 6.x, Novell client for DOS (ODI driver).

Package contains:
• PCI-Express Gigabit Ethernet card with a standard bracket,
• low profile bracket,
• multilanguage quick guide CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / BG / CN / TR / ARA,
• packed in a cardboard box.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Techninė specifikacija

Ryšys	
Ryšio technologija	Vielinis
Priimančioji sąsaja	PCI Express
Sąsaja	Eternetas
Ethernet LAN (RJ-45) portų kiekis	1
PCI versija	1.1
PCI kortos formos koeficientas	Visas aukštis (žemo profilio)
Tinklas	
Didžiausias duomenų perdavimo greitis	1000 Mbit/ai
Tinklo standartai	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u
Ethernet LAN jungtis	Taip
Eterneto sąsajos tipas	Gigabitinis eternetas
Eterneto LAN duomenų perdavimo norma	10,100,1000 Mbit/ai
Kabelių technologija	10/100/1000BaseT(X)
Wake-on-LAN pasirengimas	Taip
Pilnai abipusis (duplex)	Taip
VLAN palaikymas	Taip
LAN kontroleris	Realtek RTL8111E, Realtek RTL8111F
Konstrukcija	
Vidinis	Taip
Taikoma	PC
Lustų rinkinys	Realtek RTL8111
„Plug and Play“ funkcija	Taip
LED indikatoriai	Taip
Kilmės šalis	Kinija
Sertifikavimas	CE, RoHS
Sistemos reikalavimai	
Palaikomos „Windows“ operacinės sistemos	Taip
Palaikomos MAC operacinės sistemos	Taip
Palaikoma operacinė sistema „Linux“	Taip
Kitos palaikomos operacinės sistemos	Taip
Palaikomos serverio valdymo sistemos	Taip
Pakuotės duomenys	

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Pakuotės plotis	145 mm
Pakuotės gylis	110 mm
Pakuotės aukštis	25 mm
Paketo svoris	73 g
Pakuotės turinys	
Pridėti montavimo kronšteinai	Taip
Instrukcija	Taip
Techninė informacija	
Atitikties sertifikatai	RoHS, CE
Garantinis laikotarpis	3 metai
Matmenys ir svoris	
Matmenys (I × P × A)	3,00cm × 11,00cm × 15,00cm

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Gamintojo ir saugos informacija

GAMINTOJAS

RealQ, s.r.o.
Železná 663/5, 619 00 Brno-jih, CZ
axagon.eu

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt