Lindy 5m DP to HDMI Adapter Cable with HDR

Gamintojas: **LINDY** · Modelis: **40928** · EAN: **4002888409285** · Prekės kodas: **978422**



44.90€

Kaina su PVM

Be PVM: **37.11€**

In Stock

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Connect a DisplayPort equipped device to a 4K HDMI display or projector
- ✓ Supports high quality resolutions up to 4K@60hz
- ✓ High Dynamic Range support provides deeper blacks, brighter whites and a wider colour gamut
- ✓ Active chipset for enhanced compatibility with various graphic cards
- ✓ 2 year warranty



Aprašymas

Lindy's Active DisplayPort to HDMI Cable range combine superior performance with stylish design to provide a high quality conversion of DisplayPort 4K@60Hz signals to output to a HDMI display or projector. This range of active cables come with an in-built chipset to not only provide a reliable connection, but also enhance compatibility with both dual mode and non-dual mode graphic cards and source devices, perfect for use with DP graphics cards, laptops and PC's, while avoiding the need for additional adapters.

With support for resolutions up to 4096x2160@60Hz and with additional support for High Dynamic Range, 4K content can be viewed with crystal clear clarity, enhanced contrast and more lifelike colour. These cables are great for creating eye-catching retail displays, innovative working environments or immersive video playback in sports bars and home cinema installations, while support for uncompressed multi-channel audio allows for an impressive three-dimensional surround sound performance to compliment detailed, clear video.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Support for AMD Eyefinity technology also brings the user a cost effective way of creating a non-standard aspect ratio or ultra-high resolution display made up from up to 3 or more monitors. This feature also allows the user to run multiple applications simultaneously on separate screens, improving productivity in the workplace or creating a widescreen gaming experience.

Please note:

Audio output over HDMI is only supported when the graphics card of the notebook or desktop computer supports audio output over DisplayPort. Several on-board graphics adapters such as Mobile Intel 4 Series Express Chipset in Notebooks do NOT support audio output over DisplayPort, even when HDMI support (Intel High Definition Audio HDMI Service) is installed for audio controllers. In such instances a separate audio connection has to be set up.

Please note: Some of Nvidia's latest drivers do not work correctly at 4k@60Hz 4:4:4 when converting from DP/mDP to HDMI and will only work at 4k@60Hz 4:2:2

Techninė specifikacija

Features	
Cable length	5 m
Connector 1	DisplayPort
Connector 2	HDMI Type A (Standard)
Connector 1 gender	Male
Connector 2 gender	Male
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Gold
HDMI version	2
DisplayPort version	1.2
High Dynamic Range (HDR) supported	Yes
Maximum resolution	4096 x 2160 pixels
Supported graphics resolutions	4096 x 2160
Maximum refresh rate	60 Hz
Refresh rate at maximum resolution	60 Hz
Bend radius (min)	6 cm
Product colour	Black
Conductor material	Tinned copper
Nominal attenuation	-12dB@825-2475MHz -20dB@ 2475-4125MHz -25dB@4125-5100MHz
Jacket material	Polyvinyl chloride (PVC)
Cable type	Round cable
Connector housing material	Acrylonitrile butadiene styrene (ABS)
Connector material	Gold

AWG wire size	32
Cable shielding	Copper braid
Operational conditions	
Operating temperature (T-T)	-20 - 70 °C
Storage temperature (T-T)	-25 - 85 °C
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS, UKCA
Certification	California Proposition 65
Weight & dimensions	
Cable diameter	5 mm
Connector 1 dimensions (WxDxH)	36 x 20 x 7.5 mm
Connector 2 dimensions (WxDxH)	45.1 x 21.8 x 12.2 mm
Packaging data	
Package type	Polybag
Packaging content	
Quantity per pack	1 pc(s)
Logistics data	
Warranty period	2 year(s)
Sustainability	
Sustainability compliance	Yes

Gamintojo ir saugos informacija

MANUFACTURER

LINDY International Ltd.
Sadler Forster Way Unit 103, TS17 9JY Stockton-on-Tees, GB
lindy.com

EU RESPONSIBLE PERSON

LINDY-Elektronik GmbH
Markircher Str. 22, 68229 Mannheim, DE
lindy.com

DISTRIBUTOR

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.