APC Easy UPS On-Line nepertraukiamo maitinimo resursai (UPS) Dviguba konversija (prisijungus) 3 kVA 2700 W 6 AC išvestis(ys / čių)

Gamintojas: **APC** · Modelis: **SRVL3KRIRK** · EAN: **731304621904** · Prekės kodas: **978742**



2 908,90 €

Kaina su PVM

Be PVM: **2 404,05 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Dviguba konversija (prisijungus)
- ✓ 3 kVA 2700 W
- ✓ Signalų forma: Sinusas
- ✓ 6 AC išvestis(ys / čių)
- ✓ Ličio-jonų (Li-Ion) 48 V
- ✓ Stelažas / bokštas Juoda, Sidabras






Aprašymas

This APC Single phase Easy UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. This 3kVA double-conversion on-line lithium-ion 2U UPS provides pure sine wave power to support critical electronics during power disruptions. The SRVL comes with IEC 320 C20 input, 6x IEC 320 C13 and 1x IEC 320 C19 outlets. The On-Line UPS has a intelligent card slot for optional Network Management Card (AP9544, SRVSMB001, VGL9601I) that enables network-based UPS monitoring and management. With purchased Network Management Card and license, the UPS can connect to EcoStruxure IT or third-party centralized management platforms. The Built-in automatic and manual bypass provide seamless power to the load even in the event of an internal detected fault or error in UPS. The Emergency Power Off (EPO) function can remotely shut off the UPS in an emergency. It comes with a 5-year warranty. The SRVL comes with a easy-to-read 90 degree rotatable LCD display for detailed and accurate information on UPS status. This lithium-ion UPS is ideal for Surveillance, Co-working space, Healthcare IT, ATMs, Micro Data centers, and Server rooms.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Techninė specifikacija

Features	
UPS topology	Double-conversion (Online)
Output power capacity	3 kVA
Output power	2700 W
Waveform	Sine
Input operation voltage (min)	110 V
Input operation voltage (max)	300 V
Input frequency	40 - 70 Hz
Output operation voltage (max)	230 V
Output frequency	50/60 Hz
Surge energy rating	945 J
Heat dissipation	1024 BTU/h
Number of input phases	1
Number of output phases	1
Single-phase input voltage supported	230 V
Efficiency	90%
Crest factor	3:1
ECO mode	Yes
Emergency Power Off (EPO)	Yes
Noise level	50 dB
Audible alarm(s)	Yes
Audible alarm modes	Low battery alarm, Overload alarm
Power source type	AC
Detachable power cord	Yes
Ports & interfaces	
AC outlet types	C13 coupler, C19 coupler
Power plug	C20 coupler
AC outlets quantity	6 AC outlet(s)
USB port	Yes
USB port type	USB Type-B
Serial interface	Yes
Serial interface type	RS-232
RS-232 ports	1

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Modem (RJ-11) ports	1
Ethernet LAN (RJ-45) ports	1
Emergency Power Off (EPO) connector	Yes

Battery

Battery technology	Lithium-Ion (Li-Ion)
Battery voltage	48 V
Typical backup time at full load	9 min
Battery life (max)	10 year(s)
Battery recharge time	1.5 h
Replacement battery cartridge	RBCV183-LI

Design

Form factor	Rackmount/Tower
Product colour	Black, Silver
Rack capacity	2U
Cooling type	Active
Built-in fan	Yes
Control type	Buttons
Display type	LCD
LED indicators	Yes
International Protection (IP) code	IP20

Operational conditions

Storage temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Certificates

Waste Electrical and Electronic Equipment (WEEE) compliance	Yes
Compliance certificates	RoHS, REACH, WEEE
Certification	CB; CE; UKCA; UN 38.3; IEC 62619

Packaging content

Rack mount kit	Yes
Cables included	Output power cable, Phone (RJ-11), RJ-45, RS-232, USB cable

Weight & dimensions

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Width	438 mm
Depth	632 mm
Height	86 mm
Weight	21.2 kg
Packaging data	
Package width	600 mm
Package depth	800 mm
Package height	240 mm
Package weight	29.1 kg
Logistics data	
Customs product code (TARIC)	8504409590
Total carbon footprint (kg of CO2e)	5751.2967268825
Country of origin	Taiwan
Other features	
Input connection type	IEC 60320 C20
Output connection type	6 IEC 60320C13; 1 IEC 60320C19
Output voltage	230 V
Mounting	horizontal and vertical
Technical details	
Sustainable packaging	No
Take-back system	No
Packaging without single use plastic	No
Matmenys ir svoris	
Matmenys (I × P × A)	80,00cm × 61,00cm × 24,00cm

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas
- Atitikties deklaracija

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE
rue Joseph Monier 35, 92500 Rueil Malmaison, FR
se.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

› Atitikties deklaracija