Intellinet 28-Port L2+ Fully Managed PoE+ Switch with 24 Gigabit Ethernet Ports and 4 SFP+ Uplinks IEEE 802.3at/af (PoE+/PoE) Compliant, 370 W PoE Power Budget, Layer 2+/Layer 3 Lite, Four 10G SFP+ Open Slots, Self-Healing Network, 19" Rackmount

Gamintojas: **INTELLINET** · Modelis: **561846** · EAN: **766623561846** · Prekės kodas: **978964**



755.90€

Kaina su PVM

Be PVM: **624.71€**

In Stock

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Provides up to 24 PoE network devices with power and data
- ✓ Four small-form-factor pluggable SFP/SFP+ module slots for 10G uplink capability
- ✓ Self-Healing Network - the Powered Device Monitor feature (PDM), also known as PD Alive Check, restarts any connected PoE device that fails to respond or send out network traffic
- ✓ Domotz compatible for cloud management
- ✓ PoE power budget of 370 watts
- ✓ Power output up to 30 watts per port
- ✓ Supports VLAN (tag-based and port-based)
- ✓ 10/100/1000 auto-sensing ports that automatically detect optimal network speeds
- ✓ Supports IEEE 802.3at and IEEE 802.3af-compliant PoE devices (wireless access points, VoIP phones, IP cameras)
- ✓ Supports IEEE 802.3at/af detection and short circuit, overload and high-voltage protection






Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903





Aprašymas

28-port Gigabit Ethernet Layer 2+ Managed Switch with Four 10G Uplinks - intelligent and secure edge connectivity, ideal for small and medium enterprise networks
This 24 + 4 Layer 3 Lite Gigabit Switch is a high-performance SNMP-managed device that provides users with 24 10/100/1000 Mbps Ethernet and 4 additional 10G SFP+ ports. The Web/SNMP management provides remote control capability for flexible network management and monitoring options. Whether managed through an "in-band" SNMP management station or an Internet Web browser, this Intellinet Network Solutions Gigabit switch facilitates network administration and problem diagnosis. It can also be trunked, providing a link up to 40G to another switch.

Flexible Network Management

The Intellinet Network Solutions 28-Port Web-Managed Gigabit Ethernet Switch is easy to use and manage, having been designed to increase business productivity by reliably supporting business applications. It features a Web-based GUI and supports SNMP, RMON and Telnet. The impressive list of features includes, but is not limited to, ACL management, sophisticated QoS-related settings, port mirroring, integrated IP-connectivity tools, logging, MAC filtering, RADIUS authentication, Port aggregation and detailed port rate configuration options.

10 Gigabit Ethernet (IEEE 802.3ae)

Equipped with four 10G SFP+ open slots, this switch is the ideal solution for cost-sensitive organizations considering 10 Gigabit Ethernet. With 10G technology going mainstream and becoming ever more popular, the need for additional bandwidth has become more urgent than ever - even in smaller networks. Whether you wish to connect servers, network-attached-storage units or NVRs at 10 Gbps, or even simply connect to another gigabit switch without resorting to LACP techniques, 10G provides the solution. And in case you are not quite ready for 10G just yet, it will happily take standard 1G SFP transceiver modules until the time is right for you to make the switch.

Self-Healing Network with increased reliability and stability - Intellinet Powered Device Monitor (PDM)
This Power over Ethernet switch is equipped with Powered Device Monitoring, a self-healing PoE function. This PoE watchdog performs a PD alive check to all connected PDs and automatically resets unresponsive devices, such as PoE security surveillance cameras, by cutting off and then restoring power. The PDM function is especially useful in applications where connected devices are critical to network operation, such as in industrial or surveillance settings. As an added benefit, the PD Alive function helps eliminate unnecessary technical support calls and costly field trips by field-support engineers because the functional reboot can often bring the unresponsive device back online.

Techninė specifikacija

Management features	
Switch type	Managed
Switch layer	L2+
Quality of Service (QoS) support	Yes
Web-based management	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	24
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
SFP+ module slots quantity	4
Network	
Networking standards	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
10G support	Yes
Copper ethernet cabling technology	10BASE-TX, 100BASE-TX, 1000BASE-T
Cable types supported	Cat5e
Port mirroring	Yes
Full duplex	Yes
Half duplex	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Rate limiting	Yes
Auto MDI/MDI-X	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
Auto-sensing	Yes
Auto-negotiation	Yes
MAC address auto-learning supported	Yes
MAC address auto-aging supported	Yes
VLAN support	Yes
Virtual LAN features	Port-based VLAN, Tagged VLAN
Data transmission	
MAC address table	16000 entries
Switching capacity	128 Gbit/s
Forwarding rate	95.23 Mpps
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	12000
Packet buffer memory	12 MB
Security	
DHCP features	DHCP Option 82, DHCP client, DHCP snooping
Access Control List (ACL)	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

IGMP snooping	Yes
Protocols	
Management protocols	SNMP
Design	
Rack mounting	Yes
Form factor	1U
Product colour	Black
Housing material	Metal
Reset button	Yes
LED indicators	Activity, Link, PoE, Power
Performance	
Mean time between failures (MTBF)	90000 h
Power	
Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	425 W
Power saving mode (EEE)	Yes
Power protection features	Over voltage, Overload, Short circuit
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	370 W
Other features	
Warranty period	3 year(s)
Operational conditions	
Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	440 mm
Depth	208 mm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Height	44 mm
Weight	3 kg
Packaging content	
Cables included	AC
Manual	Yes
Rack mount kit	Yes
Packaging data	
Package type	Box
Certificates	
Compliance certificates	CE, RoHS
Certification	FCC, CE, RoHS, UKCA, NDAA
Matmenys ir svoris	
Svoris	3.77kg

Dokumentai ir vaizdo įrašai

- User manual
- Product leaflet

Gamintojo ir saugos informacija

MANUFACTURER

IC Intracom Vertriebs GmbH
Löhbacher Str. 7, D-58553 Halver, DE
intellinetnetwork.eu

DISTRIBUTOR

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt