LogiLink CQ6075S networking cable Black 5 m Cat6a S/FTP (S-STP)

Gamintojas: **LOGILINK** · Modelis: **CQ6075S** · EAN: **4052792049800** · Prekės kodas: **982999**



12.90€

Kaina su PVM

Be PVM: **10.66€**

In Stock

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ PUR patch cord for industrial use, IP20
- ✓ CAT.6A Class EA S/FTP 500 MHz 10G conform ISO/IEC 11801 & EN 50173-1
- ✓ Low smoke zero halogen conform IEC60754-2A & IEC 61034
- ✓ Oil Resistant conform EN 60811-2-1
- ✓ UV / weather resistant according to IEC60068-2-5
- ✓ Max. Operating temperature: -40° – +90° C
- ✓ Outer dimension of the cable: 6.2 mm
- ✓ Color: Black (cable and boot)

Aprašymas

Patch cable, PUR, Cat.6A, S/FTP, black, 5 m" from LogiLink Professional

LogiLink 's Cat.6A PUR patch cable is especially suitable for use in industrial environments. The abrasion-resistant sheath made of durable polyurethane (PUR) protects against external influences such as heat, oil, moisture, UV rays and other adverse influences .This high quality cable is suitable for fixed network installation and occasional free movement in dry and damp environments, and outdoors at low mechanical stress. This cable is not waterproof and not suitable for underground!

Techninė specifikacija

Features	
Cable length	5 m
Cable standard	Cat6a

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Cable shielding	S/FTP (S-STP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	Black
Connector 1 gender	Male
Connector 2 gender	Male
Jacket material	Polyurethane (PUR)
AWG wire size	27
Data transfer rate	10000 Mbit/s
Frequency	500 MHz
Suitable for outdoor use	Yes
Oil-resistant	Yes
Operational conditions	
Operating temperature (T-T)	-40 - 90 °C
Sustainability	
Doesn't contain	Halogen
Certificates	
Compliance certificates	RoHS
Certification	ISO/IEC 11801, EN50173-1, ANSI/TIA-568-C.2, IEC 60754-2, IEC 61034, EN 60811-2-1, IEC 60754
Packaging content	
Quantity per pack	1 pc(s)
Packaging data	
Package width	160 mm
Package depth	200 mm
Package weight	162 g
Logistics data	
Harmonized System (HS) code	84733080
Master (outer) case width	400 mm
Master (outer) case length	300 mm
Master (outer) case gross weight	9 kg
Master (outer) case height	300 mm
Products per master (outer) case	50 pc(s)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Dokumentai ir vaizdo įrašai

› Product leaflet

Gamintojo ir saugos informacija

MANUFACTURER

2direct GmbH
Langenstück 5, 58579 Schalksmühle, DE
info@2direct.de
2direct.de

DISTRIBUTOR

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt