ACT FB8101 networking cable Black 1 m Cat8 U/FTP (STP)

Gamintojas: **ACT** · Modelis: **FB8101** · EAN: **8716065558302** · Prekės kodas: **983227**



10.90€

Kaina su PVM

Be PVM: **9.01€**

In Stock

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Cable length: 1 meter
- ✓ CAT8 U/FTP slimline snagless patch cable with a max. bandwidth of 2000MHz (40Gbit)
- ✓ Full copper 30AWG wires, 50µ gold-plated RJ45 contacts
- ✓ Low Smoke Zero Halogen (LSZH) cable jacket reduces the risk of high concentrations of toxic gases in case of cable damage due to fire or short circuit
- ✓ Outer diameter jacket of only 5mm to improve air flow in cabinet
- ✓ For connecting two active devices e.g. a switch and a nas
- ✓ Compliant with international standards
- ✓ Cables are 100% tested
- ✓ Colour: Black











Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Aprašymas

The ACT U/FTP CAT8 datacenter slimline patch cables ensure a max. bandwidth of 2000MHz (40Gbit). The patch cables have full copper 30 AWG wires and 50u gold-plated RJ45 contacts. All cables comply with international standards and are 100% tested.

CAT8 U/FTP slimline datacenter ethernet cables are smaller in diameter (5mm vs 7.4mm) than our regular CAT8 patch cords. The bending radius is lower in comparison with regular patch cords. This results in a better airflow in the server rack/network cabinet.

The application of a LSZH (Low Smoke Zero Halogen) cable jacket reduces the risk of high concentrations of toxic gases in case the cable is damaged due to fire or short circuit.

Although, ISO/IEC and TIA standards describe the use of patch cords between 22 and 28 AWG, it is possible to use 30 AWG patch cables. This results in a higher attenuation, particularly at higher frequencies.

Techninė specifikacija

Features	
Cable length	1 m
Cable standard	Cat8
Cable shielding	U/FTP (STP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	Black
Connector 1 gender	Male
Connector 2 gender	Male
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Copper
Jacket material	Low smoke zero halogen (LSZH)
AWG wire size	30
Operational conditions	
Operating temperature (T-T)	-20 - 60 °C
Packaging content	
Quantity per pack	1 pc(s)

Gamintojo ir saugos informacija

MANUFACTURER

Intronics BV
Koolhovenstraat 1E, 3772 MT Barneveld, NL
intronics.nl

DISTRIBUTOR

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt