ACT Orange 0.25 meter LSZH U/UTP CAT6 datacenter slimline patch cable snagless with RJ45 connectors

Gamintojas: **ACT** · Modelis: **DC9152** · EAN: **8716065510416** · Prekės kodas: **983588**



8.91€

Kaina su PVM

Be PVM: **7.36€**

In Stock

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Cable length: 0.25 m
- ✓ Full copper 28AWG wires, 50µ gold RJ-45 contacts
- ✓ Outer diameter jacket of only 3.8mm to improve air flow in cabinet
- ✓ Snagless boots
- ✓ For connecting two active devices e.g. a switch and a nas
- ✓ Specifications comply to international standards
- ✓ Cables are 100% tested

Aprašymas

CAT6 U/UTP slimline datacenter ethernet cables are smaller in diameter (3.8mm vs 5.9mm) than regular CAT 6 patch cords. The bending radius is lower in comparison with regular patchcords. All this results in a better airflow in the server rack/network cabinet.

Although ISO/IEC and the TIA standards describe the use of patch cords between 22 and 26 AWG, it is possible to use 28 AWG patch cables. This results in a higher attenuation, particularly at higher frequencies.

ACT advises a maximum bundle size of 24 cables in PoE applications. In this case the temperature of the cables, that are delivering PoE deployments, will not increase. The standard, ANSI TSB-184-A, limits the maximum temperature increasement, to less than 15 degrees Celsius above the ambient temperature, for the center cable in a bundle.

Techninė specifikacija

Features	
Cable length	0.25 m

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Cable standard	Cat6
Cable shielding	U/UTP (UTP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	Orange
Connector 1 gender	Male
Connector 2 gender	Male
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Gold
Jacket material	Low smoke zero halogen (LSZH)
Cable shape	Round
AWG wire size	28
Frequency	250 MHz
Snagless cable boot	Yes
Operational conditions	
Operating temperature (T-T)	-20 - 60 °C
Weight & dimensions	
Outer diameter	3.8 mm
Packaging content	
Quantity per pack	1 pc(s)

Dokumentai ir vaizdo įrašai

› Product leaflet

Gamintojo ir saugos informacija

MANUFACTURER

Intronics BV
Koolhovenstraat 1E, 3772 MT Barneveld, NL
intronics.nl

DISTRIBUTOR

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt