ACT DA7951 networking cable Black 1.5 m Cat6a U/FTP (STP)

Gamintojas: **ACT** · Modelis: **DA7951** · EAN: **8716065572254** · Prekės kodas: **991831**



14,90 €

Kaina su PVM

Be PVM: **12,31 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Connectors: RJ45 90° angled down - RJ45 90° angled up
- ✓ Ideal for situations where space is limited without stressing the bend radius
- ✓ Full copper 32AWG wires, 50µ gold-plated RJ45 contacts
- ✓ Outer diameter jacket of only 3.8mm to improve airflow in cabinets
- ✓ Low Smoke Zero Halogen (LSZH) cable jacket reduces the risk of high concentrations of toxic gases in case of cable damage due to fire or short circuit
- ✓ Conforms to international standards
- ✓ Cables are 100% tested













Aprašymas

CAT6A U/FTP slimline datacenter patch cables are smaller in diameter (3.8mm vs 5.9mm) than regular CAT6A patch cords. The bend radius is smaller compared to standard patch cords. This results in better airflow in the server rack or network cabinet.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

The patch cable has a 90° angled down RJ45 connector to a 90° angled up RJ45 connector. Ideal for situations where space is limited without compromising the bend radius. For example in network cabinets and behind equipment.

Also available with a straight, 90° angled left or right RJ45 connector.

The use of a LSZH (Low Smoke Zero Halogen) cable jacket reduces the risk of high concentrations of toxic gases if the cable is damaged by fire or short circuit.

The ACT U/FTP patch cable has full copper 32AWG wires and 50µ gold-plated RJ45 contacts and complies with international standards.

Techninė specifikacija

Features	
Cable length	1.5 m
Cable standard	Cat6a
Cable shielding	U/FTP (STP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	Black
Connector 1 gender	Male
Connector 2 gender	Male
Connector 1 form factor	Angled
Connector 2 form factor	Angled
Connector contacts plating	Gold
Jacket material	Low smoke zero halogen (LSZH)
Conductor material	Copper
AWG wire size	32
Frequency	500 MHz
Bend radius (min)	1.5 cm
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	PoE+
Total Power over Ethernet (PoE) budget	30 W
Operational conditions	
Operating temperature (T-T)	-20 - 60 °C
Certificates	
Certification	CE
Weight & dimensions	
Outer diameter	3.8 mm

Gamintojo ir saugos informacija

GAMINTOJAS

Intronics BV
Koolhovenstraat 1E, 3772 MT Barneveld, NL
intronics.nl

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt