
ACT Red 0.25 meter LSZH U/FTP CAT6A datacenter slimline patch cable snagless with RJ45 connectors

Gamintojas: **ACT** · Modelis: **DC7552** · EAN: **8716065442410** · Prekės kodas: **991902**



10.90€

Kaina su PVM

Be PVM: **9.01€**

In Stock

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės


- ✓ Full copper 32AWG wires, 50µ gold RJ-45 contacts
- ✓ Outer diameter jacket of only 3.8mm to improve air flow in cabinet
- ✓ Snagless boots
- ✓ For channel applications
- ✓ Specifications comply to international standards
- ✓ Cables are 100% tested
- ✓ 5 Year warranty












Aprašymas

CAT6A U/FTP slimline datacenter ethernet cables are smaller in diameter (3.8mm vs 5.9mm) than regular CAT 6A patch cords. The bending radius is lower in comparison with regular patch cords. This results in a better airflow in the cabinet.
Although, ISO/IEC and TIA standards describe the use of patch cords between 22 and 26 AWG, it is possible to use 32 AWG patch cables. This results

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

in a higher attenuation, particularly at higher frequencies. ACT therefore recommends a shorter permanent link length than with regular 24 AWG patch cords. So this higher attenuation can be accommodated.
ACT advises a maximum bundle size of 24 cables in PoE applications. In this case the temperature of the cables, that are delivering PoE deployments, will not increase. The standard, ANSI TSB-184-A, limits the maximum temperature increasement, to less than 15 degrees Celsius above the ambient temperature, for the center cable in a bundle.

Techninė specifikacija

Features	
Cable length	0.25 m
Cable standard	Cat6a
Cable shielding	U/FTP (STP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	Red
Connector 1 gender	Male
Connector 2 gender	Male
Connector contacts plating	Gold
Jacket material	Low smoke zero halogen (LSZH)
Conductor material	Copper
AWG wire size	32
Frequency	500 MHz
Operational conditions	
Operating temperature (T-T)	-20 - 75 °C
Weight & dimensions	
Outer diameter	3.8 mm
Packaging content	
Quantity per pack	1 pc(s)
Logistics data	
Harmonized System (HS) code	84733080

Gamintojo ir saugos informacija

MANUFACTURER

Intronics BV
Koolhovenstraat 1E, 3772 MT Barneveld, NL
intronics.nl

DISTRIBUTOR

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt