SMALLRIG RC 60B 60W LED Studio Light

Gamintojas: **SMALLRIG** · Modelis: **4376B** · EAN: **6941590026633** · Prekės kodas: **997363**



234,90 €

Kaina su PVM

Be PVM: **194,13 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt






Aprašymas

SMALLRIG RC 60B 60W LED Studio Light

The SmallRig RC 60B is a compact 60 W COB LED light equipped with a built-in rechargeable battery, color temperature adjustment from 2700–6500 K, and high color rendering indices of CRI 97+ and TLCI 98+. At 5600 K, it delivers 2,670 lux from a distance of 1 m without an additional reflector; with the included 45° Mini Hyper Reflector, this value increases to 11,200 lux. The body weighs approximately 650 g, and its compact size, battery-powered operation, and compatibility with a handheld grip make the RC 60B well-suited for both studio shoots and on-location productions.

Built-in Battery and Flexible USB-C Power Supply

The built-in 49.64 Wh battery allows you to use the light without having to install additional NP-F or V-Mount batteries and their associated mounts and cables. At full power, the light can operate for approximately 45 minutes, and in ECO mode, the runtime extends to about 75 minutes, making it easier to handle shorter shoots without access to a power outlet. The USB-C port supports PD charging up to 100 W, with a maximum battery charging power of 48 W; the ability to operate while charging allows the light to be powered by compatible PD power supplies or power banks with a recommended power rating of 65 W or higher.

Adjustable Color Temperature and Precise Colors

The color temperature range from 2700 to 6500 K allows you to adapt the lighting to various conditions, from warm indoor light to cooler light similar to daylight. CRI 97+, TLCI 98+, an average SSI of 89, and TM-30 Rf 96 and Rg 100 help preserve the natural appearance of colors, skin tones,

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

and photographed subjects. As a result, the RC 60B is suitable for, among other things, recording interviews, online content, commercials, and news reports, as well as for product and portrait photography and event coverage.

Simple Adjustment and Quiet Cooling System

The light features separate dials for adjusting color temperature and light intensity, allowing you to quickly change key settings without navigating through complex menus. A 1.3-inch LED screen makes it easy to monitor current settings while working and allows you to adjust the light more efficiently for the shot you're preparing. An intelligent cooling system minimizes overheating, and the fan operates at approximately 26 dB in standard mode and approximately 23 dB in ECO mode—a key consideration when recording footage with audio.

Lightweight design built for field use

The housing is made of V0-rated flame-retardant PC+ABS plastic and features a metal base, which helps reduce the unit's weight while maintaining adequate durability during regular use. The body itself measures approximately 115 × 85 × 85 mm and weighs about 650 g, while the entire set, including accessories and a carrying case, weighs about 1.5 kg. The included handheld grip, tripod adapter, Mini Hyper Reflector 45°, and carrying bag make it easy to use the light in various configurations and conveniently transport it between shooting locations.

Included in the set

- SmallRig RC 60B LED Light
- Mini Hyper Reflector 45°
- 3 m USB-C to USB-C PD cable
- Lighting tripod adapter
- Handheld grip
- Protective cover
- Carrying bag
- User manual

Manufacturer	SmallRig
Model	RC 60B (4376B)
Light source type	COB LED
Rated power	60 W
Maximum power	63 W
Color temperature range	2,700–6,500 K ±200 K
Illuminance without reflector	2,670 lx at 1 m / 5,600 K
Illuminance with 45° Mini Hyper Reflector	11,200 lx at 1 m / 5,600 K
CRI	97+
TLCI	98+
Average SSI	89
TM-30 Rf	96
TM-30 Rg	100
Control method	controls on the housing
Display	1.3" LED
Power Supply	Built-in battery / PD charger / PD power bank

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Battery	14.6 V / 3,400 mAh / 49.64 Wh
Run time at maximum power	Approximately 45 minutes
Run time in ECO mode	approximately 75 minutes
Maximum USB-C PD input power	100 W
Maximum battery charging power	48 W / 3 A
Fan noise level	approximately 26 dB in standard mode
Fan noise level in ECO mode	approximately 23 dB
Material	V0-rated flame-retardant PC+ABS plastic + metal
Body dimensions	115 × 85 × 85 mm
Weight	650 g

GPSR Link: https://psr-assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photographic_studio.pdf, PPWR: https://ppwr.innpro.pl/en/smallrig, Gross weight: 4440, Net weight: 650, Box length: 30,00, Box width: 26,50, Box height: 11,00, Last delivery: 05.11.2026

Techninė specifikacija

Matmenys ir svoris	
Matmenys (I × P × A)	30,00cm × 26,00cm × 11,00cm
Svoris	4,44kg