Axagon ADE-AM15 USB-A Gigabit Ethernet adapter with integrated CAT6 RJ-45 network cable (1.5 m)

Gamintojas: **AXAGON** · Modelis: **ADE-AM15** · EAN: **8595247909657** · Prekės kodas: **997598**



15,90 €

Kaina su PVM

Be PVM: **13,14 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wired
- ✓ USB 3.2 Gen 1 (3.1 Gen 1) Ethernet
- ✓ Gigabit Ethernet, Fast Ethernet 5000 Mbit/s
- ✓ Chipset: ASIX AX88179



















Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Aprašymas

Gigabit Ethernet connection via USB-A up to 1 Gbps

With the external USB network adapter AXAGON ADE-AM15, you can easily connect devices (notebook or computer) to the internet or local LAN network. Just plug it into the device’s USB-A port and connect the integrated CAT6 network cable with the RJ-45 connector directly into the network. Without an additional Ethernet cable, you get a stable wired connection with speeds up to 1 Gbps, all without installing drivers. Compared to Wi-Fi, a wired connection offers lower latency, more stable data transmission, and higher internet connection reliability.

The adapter also supports advanced network features such as Wake-on-LAN, VLAN, Jumbo Frames, or precise PTP/gPTP time synchronization. It is ideal for working from home, video conferencing, fast backup to NAS, or gaming (e.g., Nintendo Switch with a wired connection). It is also suitable for situations where a notebook or other device does not have a LAN port or its port is damaged.

Direct network connection thanks to 1.5 m CAT6 cable

The F/UTP CAT6 network cable with a length of 1.5 meters allows convenient connection even to a more distant network outlet. You can easily plug the adapter directly without additional extension cables, whether on a desk, meeting room, or at home. The cable can be simply hidden in a cable duct and left permanently connected to the data outlet. For maximum flexibility, it is also available in other lengths and USB-C cable variants.

Stable connection for NAS, data transfer, and online work

The adapter supports transfer speeds up to 1 Gbps (10/100/1000 Mbps) and can be used, for example, for backing up data to a network disk (NAS), transferring large files between devices, or connecting to corporate networks with higher data traffic. The wired connection additionally eliminates dropouts and signal fluctuations typical for Wi-Fi.

Wake-on-LAN, VLAN, Jumbo Frames, and PTP for advanced networks

The network card with ASIX AX88179B chip offers a range of advanced functions for home and corporate networks. Wake-on-LAN allows remote waking of a computer, VLAN (IEEE 802.1Q) is used to separate network traffic, and Jumbo Frames up to 9 kB can improve the efficiency of transferring large amounts of data, for example between a computer and NAS. Support for IEEE 802.1P enables prioritization of network traffic and PTP (IEEE 1588v2) and gPTP (IEEE 802.1AS) provide precise time synchronization of devices in the network. The IPv4/IPv6 Checksum Offload and TCP Large Send Offload technologies offload part of the network communication processing to the adapter, helping to reduce CPU load. It also features AUTO-MDIX, which automatically detects cable connection type.

Wide compatibility without driver installation

The network adapter/cable supports Windows, macOS, Linux, iPadOS, iOS, and Android operating systems. Thanks to automatic installation, just connect the adapter and you can use it immediately without the need to install drivers. It is easy to use with desktop computers, notebooks, ultrabooks, tablets, or mobile phones that support wired Ethernet connection. It is also compatible with the Nintendo Switch gaming console, making it a simple way to ensure stable wired connection while gaming. To connect to devices with USB-C, a suitable USB-A adapter can be used, for example AXAGON RUCM-AFA.

Aluminum body, durable braid, and quality shielding

The elegant aluminum body reliably protects electronics from mechanical damage, and the durable cable braid increases resistance to everyday use. The aluminum body also effectively dissipates heat generated during operation. Quality shielding with foil and grounding conductor minimizes electromagnetic interference and contributes to stable data transmission. Because of this, the adapter is a reliable choice even in environments with increased electromagnetic interference, such as offices, server rooms, or industrial facilities.

Input (connection to notebook):
• USB 5Gbps (USB 3.2 Gen 1 / USB 3.0), USB-A male connector,
• compatible with USB 480Mbps, USB 10Gbps, USB 20Gbps, USB 40Gbps, and Thunderbolt 3/4/5.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Output:
• Gigabit Ethernet interface, RJ-45 male connector,
• supported Ethernet interface transfer speeds 10/100/1000 Mbps,
• supported IEEE 802.3i 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3ab 1000BASE-T specifications,
• 10/100/1000 Mbps autodetection,
• support for IPv4/IPv6 Packet Checksum Offload Engine (COE) to reduce CPU load including IPv4 IP/TCP/UDP/ICMP/IGMP & IPv6 TCP/UDP/ICMPv6 checksum checking and generation,
• support for TCP Large Send Offload V1 and V2,
• support for IEEE 802.1P Layer 2 Priority Encoding and Decoding,
• support for IEEE 802.1Q VLAN tagging,
• support for filtering up to 4096 VLAN IDs,
• support for IEEE 802.3az EEE (Energy Efficient Ethernet) – power reduction in idle state,
• support for IEEE 802.3 Annex.31B Flow Control,
• support for IEEE 1588v2 PTP (Precision Time Protocol) and IEEE 802.1AS gPTP (Generalized Precision Time Protocol),
• support for up to 9K Jumbo Frame,
• support for L2 MAC address filtering,
• support for L3/L4 IPv4/IPv6 IP/Port filtering,
• support for Auto-MDI/MDIX – crossover detection and autocorrection eliminates the need for crossover cables.

Additional features:
• F/UTP Cat6 cable,
• full Plug and Play and Hot Plug support,
• CDC-ECM support for automatic driver installation across different OSes,
• CDC-NCM support for native driverless installation on iOS/iPadOS/macOS/Linux,
• iPXE support for network booting,
• USB bus power – no additional power supply needed,
• support for direct connection between two devices (point-to-point, without the need for a switch or router),
• ASIX AX88179B chipset.

Wake-on-LAN support in various modes:
• Support for sleep mode and remote wake-up via Magic Packet, Microsoft Wake-up Frame, and Link Change wake-up,
• Bonjour Wake-on-Demand support,
• Wakeup Packet Indication support,
• Microsoft Modern Standby support.

Advanced Power Management features:
• Power Management Offload support (ARP and NS),
• IEEE 802.3az EEE (Energy Efficient Ethernet) support,
• ECMA-393 proxZzzy® standard support for managing network connectivity of sleeping hosts via proxy servers.

Other details:
• Dimensions of active part with USB-A: 65 × 18 × 8 mm (W × D × H)
• Outer cable diameter: 5 mm
• Conductors: 28 AWG
• Cable length: 1.5 m
• Weight: 58 g

Supported operating systems:
• Windows (min. 8.1 and later), macOS, Linux, iPadOS, iOS, Android, Nintendo Switch system software.
• To connect mobile phones, tablets, and other devices with USB-C, a suitable USB-A adapter can be used, for example AXAGON RUCM-AFA.

Package contents:
• 1.5 m long USB-A – RJ-45 Gigabit Ethernet cable,
• multilingual manual CZ / DE / DK / ENG / ESP / EST / FIN / FR / GR / HR / HU / IT / LT / LV / NL / NOR / PL / PT / RO / SK / SLO / SRB / SWE / TR / UA / ALB / BG / BOS / CN / ARA,

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

• packed in a cardboard box with a hanging hole.

Techninė specifikacija

Ports & interfaces	
Connectivity technology	Wired
Host interface	USB
Interface	Ethernet
Ethernet LAN (RJ-45) ports	1
USB version	3.2 Gen 1 (3.1 Gen 1)
Network	
Maximum data transfer rate	5000 Mbit/s
Networking standards	IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.1Q, IEEE 802.3az, IEEE 802.3
Ethernet LAN	Yes
Ethernet interface type	Gigabit Ethernet, Fast Ethernet
Ethernet LAN data rates	10,1000,100 Mbit/s
Wake-on-LAN ready	Yes
Jumbo frames support	Yes
VLAN support	Yes
Design	
Internal	No
Product colour	Grey
Chipset	ASIX AX88179
Plug and Play	Yes
Country of origin	China
Certification	CE, RoHS, Reach
Power	
USB powered	Yes
System requirements	
Windows operating systems supported	Yes
Mac operating systems supported	Yes
Linux operating systems supported	Yes
Other operating systems supported	Yes
Weight & dimensions	

Width	65 mm
Depth	18 mm
Height	8 mm
Weight	58 g
Packaging data	
Package width	150 mm
Package depth	90 mm
Package height	30 mm
Package weight	90 g
Packaging content	
Cables included	LAN (RJ-45), USB
Manual	Yes
Technical details	
Compliance certificates	REACH, RoHS, CE
Warranty period	3 year(s)
Matmenys ir svoris	
Matmenys (I × P × A)	18,00cm × 10,00cm × 3,00cm

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Gamintojo ir saugos informacija

GAMINTOJAS

RealQ, s.r.o.
Železná 663/5, 619 00 Brno-jih, CZ
axagon.eu

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.